



## Catalog No. 2TLA020007R6900

**Description: JSTD25K TWOHAND CONTROL** 

UPC No 7350024479690

Home > Machine Safety > Safety Control Devices

Two-hand device with two JSTD1-B Safeballs and one emergency stop button Smile 10 EK. Each Safeball is mounted on a side of a 44x88 extruded aluminum profile designed for two-hand applications. The Smile 10 EK emergency stop button is mounted on top. Safeballs and Smile are pre-wired to a M12-8 male connector. The safeballs have protective flanges.

Descriptors	
Category	Safety Control Devices
Туре	Two Hand Station
Specifications	
Product Class	One and Two Hand Control Devices
Product Main Type	JSTD25
Supply Voltage	24VDC
Degree of Protection	IP65
Classifications	
ETIM 4	EC001260 - Two-hand control device
ETIM 5.0	EC001260 - Two-hand control device
ETIM 6.0	EC001260 - Two-hand control device
ETIM 7	EC001260 - Two-hand control device
ETIM 8 (Etim8)	EC001260 - Two-hand control device
Dimensions	
Product Net Depth / Length	90.5 mm
Product Net Height	189 mm
Product Net Width	364 mm
Product Net Weight	1.52kg
Safety Information	
Performance Level	Up to e

electrification.us.abb.com Created on: 09/30/2024