



Representative

Catalog Number: SAC 2/0 R 1/0 TN
Product ID: 7TAA262050R0319
UPC Number: 78378674748
Status: Active

Tin-Plated Aluminum Compression Reducer - Common Die Series, for Aluminum or Copper Conductors, Side A: Concentric 2/0, Compressed 2/0, Compact 3/0, Solid 3/0, Side B: Concentric 1/0, Compressed 1/0 Compact 2/0, Solid 2/0, Installing Dies 840, 249, TX, CSA 24

- Install with Six Common Dies to Reduce Your Die Inventory.
- Dual-Rated for Use with Aluminum and Copper Conductors.
- Bores Coated with Oxide Inhibitor to Prevent Oxidation.
- Marked with Conductor Sizes and Die References for Easy Identification.
- Meets or Exceeds ANSI C119.4 Specifications.

North American Specifications (UNSPSC)

UNSPSC	39121448 Wire or cable compression connector
IGCC	4668 Wire or cable compression connector
Brand Name	Blackburn
Type	Aluminum Straight Reducing Splices
Special Features	Dual Rated. Prefilled with Oxide Inhibitor. Marked with Conductor sizes and Die References for easy Identification.
Application	Reducers for general UnderGround applications.
Standard	ANSI C119.4
Size	4 inch long
Conductor Range	2/0 Concentric and Compressed, 3/0 Compact and Solid to 1/0 Concentric and Compressed, 2/0 Compact and Solid
Material	Aluminum
Finish	Tin Plated
Insulation	None

Packaging

Outer Quantity	100
Outer Dimensions (inches)	1x1x1
Weight Uom	1 lbs. Each

Documents / Support Tools

Safety Data Sheet (SDS) Global	SDS-00041-TB2
--------------------------------	---------------

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
 www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com