




Metal Clad Cable Termination Fittings & Accessories T&B Catalog Number:

ST075-467SS 78621057132

Status: Active

Description:

Star Teck stainless steel jacketed cable fitting hub size 3/4 inch Range over jacket 0.880-1.065 inch.



| Features | |
|-------------------------------------|--|
| | Easy Installation-Exclusive power-grip. Provides a grip that's high up on the cable-not on the first convolution-so strip length and cutting of cable are not critical. |
| | Dependable Service-stainless steel retaining ring. Withstands corrosive environments. Non-magnetic. |
| | Dependable Grounding-Power-Grip grounding ring is non-magnetic stainless steel. Provides 360° long-term dependable grounding. It makes immediate contact with the cable. |
| | Watertight-Tapered bushing. Cone shaped to provide a secure, tight fit while eliminating cupping or water in vertical installations. |
| | Easy to Install In Tight Spaces-Low profile glad nut fits tight spaces. Has grooves for screwdriver installation, and flats for a wrench. Durable and reusable with funnel entry for easy cable insertion. |
| Application | , , |
| | Provides means for passing armored, metal clad, jacketed cable through a bulkhead or enclosure in hazardous areas. (these fittings are suitable for hazardous areas when used with T&B sealing compound). |
| | Form a mechanical grip and water and/or oil-resistant termination. |
| | Provide grounding continuity of cable armor. |
| General | |
| Material | Stainless Steel |
| Dimension Information | |
| Hub Size (inches) | 3/4 |
| Dimension A (inches) | 0.819 |
| Dimension B (inches) | 2.450 |
| Dimension C (inches) | 2.080 |
| Range Over Jacket -Minimum (inches) | 0.880 |
| Range Over Jacket -Maximum (inches) | 1.065 |
| Range Over Armor -Minimum (inches) | 0.770 |
| Range Over Armor -Maximum (inches) | 0.985 |
| Packaging | |
| Package in Units | 10 |
| | |



| T&B Sold in UOM | Each |
|-----------------------------------|----------------------|
| T&B Weight Per UOM | 62.5 lbs. per 100 |
| Application Support | |
| | |
| T&B Instruction Sheets | ta00904-tb2 |
| Product Specifications & Overview | Available on Website |
| Certifications | |
| RoHS Compliance | Yes |
| • | 103 |
| Certifications | |



File Nbr: E 38947

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com