

\*\*\*Spare part\*\*\* SIPLUS LOGO! 24RC -25...+70 °C based on 6ED1052-1HB00-0BA6



Figure similar

Display		
with display		Yes; The display is bright at temperatures below 0 °C and dark at temperatures over +55 °C. This procedure is self-reversing on returning to the standard temperature range (0 °C to +55 °C).
Installation type/mounting		
Mounting		on 35 mm DIN rail, 4 spacing units wide
Supply voltage		
Rated value (DC)		
• 24 V DC		Yes
permissible range, lower limit (DC)		20.4 V; 22 V @ >55 °C
permissible range, upper limit (DC)		28.8 V; 27.5 V @ >55 °C
Rated value (AC)		
• 24 V AC		Yes
Time of day		
Time switching clocks		
• Power reserve		80 h

<b>Digital inputs</b>	
Number of digital inputs	8
<b>Digital outputs</b>	
Number of digital outputs	4; Relays
Short-circuit protection	No; external fusing necessary
<b>Relay outputs</b>	
Switching capacity of contacts	
— with inductive load, max.	3 A; 1 A per relay @ > 55 °C; 3 A per relay @ > 55 °C & < 15 s
— with resistive load, max.	10 A; 3 A per relay @ > 55 °C; 10 A per relay @ > 55 °C & < 15 s
<b>EMC</b>	
Emission of radio interference acc. to EN 55 011	
• Limit class B, for use in residential areas	Yes
<b>Degree and class of protection</b>	
Degree of protection acc. to EN 60529	
• IP20	Yes
<b>Standards, approvals, certificates</b>	
CSA approval	No
UL approval	Yes; File: E120869 // Tmax = 55 °C
FM approval	No
developed in accordance with IEC 61131	Yes
according to VDE 0631	Yes
Marine approval	No
<b>Ambient conditions</b>	
Ambient temperature during operation	
• min.	-25 °C; = Tmin
• max.	70 °C; = Tmax; 55 °C @ UL/cUL use
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost permitted (no commissioning in bedewed state)
<b>Resistance</b>	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *

— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
<b>Use on ships/at sea</b>	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
<b>Remark</b>	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
<b>Conformal coating</b>	
• Coatings for printed circuit board assemblies acc. to EN 61086	Yes; Class 2 for high availability
• Military testing according to MIL-I-46058C, Amendment 7	Yes; Discoloration of coating possible during service life
<b>Dimensions</b>	
Width	72 mm
Height	90 mm
Depth	55 mm
<b>last modified:</b>	08/15/2019