



Item # 20017564, FLEXWING SUPER Petroleum Transfer Hose 4 in x 400 ft, 250 PSI, Black

APPLICATION: A premium high pressure petroleum transfer hose for handling ethanol blends, gasoline, oils and other petroleum products at higher working pressures.

CONSTRUCTION TUBE: Special fuel-resistant Black nitrile synthetic rubber RMA Class A (High Oil Resistance)

COVER: Black Neoprene synthetic rubber RMA Class A (High Oil Resistance), wrapped finish

REINFORCEMENT: Spiral-plied synthetic fabric with wire helix

TEMPERATURE: -35 °F to 200 °F (-37 °C to 93 °C)

COUPLINGS: Use Continental Contitech Insta-Lock Cam & Groove Fittings with this product.

BRANDING: Example: Continental Contitech Flexwing® Petroleum Hose.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Petrol Transfer
Style	Petrol Transfer Hose
Construction Tube	Special fuel-resistant Black nitrile synthetic rubber RMA Class A (High Oil Resistance)
Cover	Black Neoprene synthetic rubber RMA Class A (High Oil Resistance), wrapped finish
Reinforcement	Spiral-plied synthetic fabric with wire helix

Color	Black
Min. Temperature	-35 °F -37 °C
Max. Temperature	200 °F 93 °C
Max. Working Pressure	300.0 psi 1.72 MPa
Brand	PLICORD® SUPER BLACK FLEXWING®
Order Code	543-117

Specifications

I.D.	4 in 101.60 mm
Nom. O.D.	4.830 in 122.70 mm
Total Width	4.830 in 122.70 mm
Length	400.000 ft
Bend Radius	10.000 in 254.00 mm
Vacuum Rating	29.000 inHg 737.00 mmHg
Weight	3.760 lb/ft 5.60 kg/m

MideastUS@contitech.us
 1-800-235-4632
 Contitech.us

ContiTech