



## Item # 20017580, PYROFLEX ASPHALT Transfer Hose 4 in x 100 ft, 150 psi, Black

**APPLICATION:** For the transfer of high temperature petroleum based materials such as tar, asphalt, and hot oils. It is suitable for suction and discharge service on tank trucks, tank cars or at bulk stations. Heat resistant tube and Flexten reinforcement. (Hot oils only rated to 200 °F).

**CONSTRUCTION TUBE:** Black Nitrile (special heat resistant) synthetic rubber RMA Class A (High Oil Resistance)

**COVER:** Black Wingprene® synthetic rubber RMA Class A (High Oil Resistance) with spiral red stripe

**REINFORCEMENT:** Spiral-plied Flexten® with wire helix

**TEMPERATURE:** -25 °F to 350 °F (-32 °C to 177 °C)

**COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

**BRANDING (SPIRAL):** Example: Continental Contitech Pyroflex Hot Tar and Asphalt II 150 psi.



[Product Specifications](#) | [Specifications](#)

### Product Specifications

Type	Petrol Transfer
Style	Petrol Transfer Hose
Construction Tube	Black Nitrile (special heat resistant) synthetic rubber RMA Class A (High Oil Resistance)
Cover	Black Wingprene® synthetic rubber RMA Class A (High Oil Resistance) with spiral red stripe

<b>Reinforcement</b>	Spiral-plied Flexten® with wire helix
<b>Color</b>	Black
<b>Min. Temperature</b>	-25 °F 350 °C
<b>Max. Temperature</b>	-32 °F 177 °C
<b>Max. Working Pressure</b>	150.0 psi 1.03 MPa
<b>Brand</b>	PYROFLEX® HOT TAR & ASPHALT II
<b>Packaging</b>	Coiled, Polywrapped
<b>Order Code</b>	543-118

### Specifications

<b>I.D.</b>	4 in 101.60 mm
<b>Nom. O.D.</b>	4.680 in 118.80 mm
<b>Total Width</b>	4.680 in 118.80 mm
<b>Length</b>	400.000 ft
<b>Bend Radius</b>	10.000 in 254.00 mm
<b>Vacuum Rating</b>	29.000 inHg 737.00 mmHg
<b>Weight</b>	2.910 lb/ft 4.34 kg/m

[MideastUS@contitech.us](mailto:MideastUS@contitech.us)  
 1-800-235-4632  
 Contitech.us

**ContiTech**