



Item # 20017767, FUEL DISCHARGE Transfer Hose 4 in x 400 ft, 150 PSI, Black

APPLICATION: Plicord® Fuel Discharge hose is for the discharge of gasoline, oil, ethanol blends and other petroleum based products in tank and industrial applications.

CONSTRUCTION TUBE: Nitrile synthetic rubber RMA Class A (High Oil Resistance), plus antistatic wires

COVER: Black Chemivic™ synthetic rubber RMA Class A (High Oil Resistance)

REINFORCEMENT: Spiral-plied synthetic fabric (2"–4": 2 ply; 6": 4 ply), plus grounding wires

TEMPERATURE: -35 °F to 18 0°F (-37 °C to 82 °C)

COUPLINGS: Use Continental Contitech Insta-Lock Cam & Groove Fittings with this product.

BRANDING (SPIRAL): Example: Continental Contitech Plicord® Fuel Discharge.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Petrol Transfer
Style	Petrol Transfer Hose
Construction Tube	Nitrile synthetic rubber RMA Class A (High Oil Resistance), plus antistatic wires
Cover	Black Chemivic™ synthetic rubber RMA Class A (High Oil Resistance)
Reinforcement	Spiral-plied synthetic fabric (2"–4": 2 ply; 6": 4 ply), plus grounding wires
Color	Black

Min. Temperature	-35 °F -37 °C
Max. Temperature	180 °F 82 °C
Max. Working Pressure	150.0 psi 1.03 MPa
Brand	PLICORD® FUEL DISCHARGE
Order Code	543-331

Specifications

I.D.	4 in 101.60 mm
Nom. O.D.	4.520 in 114.80 mm
Total Width	4.520 in 114.80 mm
Length	400.000 ft
Weight	1.910 lb/ft 2.84 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech