



Item # 20018001, FLEXWING ARCTIC Petroleum Transfer Hose 2 in x 100 ft, 150 psi, Blue

APPLICATION: Plicord® Arctic Flexwing® is for use in low-temperature operations for transferring gasoline, oil and other petroleum products.

CONSTRUCTION TUBE: Ultra-low temperature oil resistant synthetic rubber RMA Class A (High Oil Resistance)

COVER: Blue ultra-low temperature synthetic rubber RMA Class A (High Oil Resistance) with red spiral stripe. Smooth cover, wrapped finish

REINFORCEMENT: Spiral-plyed synthetic fabric with wire helix

TEMPERATURE: -65 °F to 180 °F (-54 °C to 82 °C)

COUPLINGS: Use Continental Contitech Insta-Lock Cam & Groove Fittings with this product.

BRANDING (SPIRAL): Example: Continental Contitech Arctic Flexwing® 150 psi WP.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Petroleum Transfer
Style	Petrol Transfer Hose
Construction Tube	Ultra-low temperature oil resistant synthetic rubber RMA Class A (High Oil Resistance)
Cover	Blue ultra-low temperature synthetic rubber RMA Class A (High Oil Resistance) with red spiral stripe. Smooth cover, wrapped finish

Reinforcement	Spiral-plyed synthetic fabric with wire helix
Color	Blue
Min. Temperature	-65 °F -54 °C
Max. Temperature	180 °F 82 °C
Max. Working Pressure	150.0 psi 1.03 MPa
Brand	PLICORD® ARCTIC FLEXWING®
Packaging	Coiled, Polywrapped
Order Code	543-650

Specifications

I.D.	2 in 50.80 mm
Nom. O.D.	2.500 in 63.50 mm
Length	100.000 ft
Bend Radius	5.000 in 127.00 mm
Vacuum Rating	29.000 inHg 737.00 mmHg
Weight	1.070 lb/ft 1.59 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech