



## Item # 20021789, REDWING Fuel Oil Dispensing Hose FxF 1 3/8 in x 1 ft, 250 PSI, Red

**APPLICATION:** Redwing® Fuel Oil is for transfer and delivery of fuel oil and petroleum products for home delivery, commercial and industrial service. Redwing Fuel Oil has two textile braids. The braided construction reduces kinking and twisting when reeling. The smooth cover has low drag resistance.

**CONSTRUCTION TUBE:** Nitrile synthetic rubber (ORS)

**COVER:** Red Chemivic™ synthetic rubber (smooth finish) (ORS)

**REINFORCEMENT:** Braided (2) synthetic yarn

**TEMPERATURE:** -40 °F to 140 °F (-40 °C to 60 °C)

**COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

**BRANDING:** Example: 1" (25.4 mm) 2 BD Redwing® Fuel Oil Continental Contitech. Made in USA.



[Product Specifications](#) | [Specifications](#)

### Product Specifications

Type	Oil Transfer
Style	Redwing Fuel Oil Dispense Hose
Construction Tube	Nitrile synthetic rubber (ORS)
Cover	Red Chemivic™ synthetic rubber (smooth finish) (ORS)
Reinforcement	Braided (2) synthetic yarn
Color	Red

<b>Min. Temperature</b>	-40 °F -40 °C
<b>Max. Temperature</b>	140 °F 60 °C
<b>Max. Working Pressure</b>	250.0 psi 1.72 MPa
<b>Brand</b>	REDWING®
<b>Order Code</b>	532-016

### Specifications

<b>I.D.</b>	1 3/8 in 34.90 mm
<b>Nom. O.D.</b>	1.880 in 47.80 mm
<b>Total Width</b>	1.880 in 47.80 mm
<b>Length</b>	1.000 ft
<b>Weight</b>	0.700 lb/ft 1.04 kg/m
<b>Weight</b>	155.706 lb

[MideastUS@contitech.us](mailto:MideastUS@contitech.us)

1-800-235-4632

Contitech.us

**ContiTech**