



Item # 20023820, WHITEWATER Pressure Washer Service 1/2 in x 500 ft, 2500 PSI, Black

APPLICATION: For use on either steam cleaner machines or combination steam cleaner/pressure washer machines.

CONSTRUCTION TUBE: Pyrosyn® synthetic rubber

COVER: Black and Red Hysunite™ synthetic rubber, RMA Class B (Medium Oil Resistance)

REINFORCEMENT: Braided (1) steel wire

TEMPERATURE: Handles hot water at 325 °F/163 °C and 350 psi for Steam Cleaning Service, handles hot water at 250 °F/121 °C and 3000 psi (2500 psi on 1/2") for Pressure Washer Service

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Example: Continental Contitech 3/8" Whitewater® Pressure Washer 3000 psi/250 °F Steam Cleaner 350 psi/325 °F. Made in USA.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Style	Cleaning Equipment Hose
Construction Tube	Pyrosyn® synthetic rubber
Cover	Black Hysunite™ synthetic rubber, RMA Class B (Medium Oil Resistance)
Reinforcement	Braided (1) steel wire
Color	Black

Max. Temperature	250 °F 121 °C
Max. Working Pressure	2500.0 psi 17.24 MPa
Packaging	Reel
Order Code	539-095
Edited By: Initials and Date	SAS 12/11/12
Brand	WHITEWATER®

Specifications

I.D.	1/2 in 12.70 mm
Nom. O.D.	0.830 in 21.20 mm
Length	500.000 ft
Weight	0.310 lb/ft 0.46 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech