



Item # 20026512, SURELINE Multipurpose Hose 1 1/2 in x 300 ft, 150 PSI, Black

APPLICATION: For a wide range of industrial, construction, and agricultural water discharge applications in which a general-service water hose is needed.

CONSTRUCTION TUBE: EPDM(compound)® synthetic rubber, RMA Class C (limited oil resistance)

COVER: Red or Black EPDM(compound) synthetic rubber

REINFORCEMENT: Spiral synthetic yarn

TEMPERATURE: -40 °F to 190 °F (-40 °C to 88 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Example: 1/2" Sureline® Continental Contitech 150 psi WP.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Multipurpose Transfer
Style	Multipurpose Hose
Reinforcement	Spiral synthetic yarn
Cover	Black Versigard® synthetic rubber
Construction Tube	Versigard® synthetic rubber, RMA Class C (limited oil resistance)
Color	Black
Min. Temperature	-40 °F

	-40 °C
Max. Temperature	190 °F 88 °C
Max. Working Pressure	150.0 psi 1.03 MPa
Packaging	Reel
Brand	SURELINE®
Order Code	569-049

Specifications

I.D.	1 1/2 in 38.10 mm
Nom. O.D.	1.880 in 47.80 mm
Length	300.000 ft
Weight	0.680 lb/ft 1.01 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech