



## Item # 20026583, ORTAC® 300 Multipurpose Hose 1 1/2 in x 300 ft, 300 PSI, Red

**APPLICATION:** Ortac® (Oil Resistant Tube and Cover) is our most popular premium-quality multipurpose hose. Used in the most abusive industrial applications, Ortac will handle air, oil, water, kerosene and some chemicals. Nonconductive, minimum electrical resistance greater than one (1) megohm per inch of hose length; at 1000 Volts DC. Available in 250, 300 and 400 psi working pressures. NOTE: Ortac 400 Yellow is USMSHA approved.

**CONSTRUCTION TUBE:** Nitrile synthetic rubber, RMA Class A (high oil resistance)

**COVER:** Red or Yellow Carbryn™ synthetic rubber, RMA Class A (high oil resistance)

**REINFORCEMENT:** Spiral synthetic yarn, 2" is braided

**TEMPERATURE:** -20 °F to 190 °F (-29 °C to 88 °C)

**COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

**BRANDING:** Example: 1 1/2" (38.1 mm) Ortac® 300 psi WP. Made in USA Continental Contitech.



[Product Specifications](#) | [Specifications](#)

### Product Specifications

Type	Multipurpose Transfer
Style	Multipurpose Hose
Reinforcement	Spiral synthetic yarn, 2" is braided
Cover	Red Carbryn™ synthetic rubber, RMA Class A (high oil resistance)
Construction Tube	Nitrile synthetic rubber, RMA Class A (high oil resistance)

<b>Color</b>	Red
<b>Min. Temperature</b>	-20 °F -29 °C
<b>Max. Temperature</b>	190 °F 88 °C
<b>Max. Working Pressure</b>	300.0 psi 2.07 MPa
<b>Packaging</b>	Reel
<b>Brand</b>	ORTAC®
<b>Order Code</b>	569-059

### Specifications

<b>I.D.</b>	1 1/2 in 38.10 mm
<b>Nom. O.D.</b>	2.080 in 52.80 mm
<b>Length</b>	300.000 ft
<b>Weight</b>	0.880 lb/ft 1.31 kg/m

[MideastUS@contitech.us](mailto:MideastUS@contitech.us)

1-800-235-4632

Contitech.us

**ContiTech**