



Item # 20028867, PACER Gasoline Lightweight Dispensing Hose 559N 1 in x 450 ft RL

APPLICATION: For all types of gasoline dispensing applications where flexibility and a lightweight hose is desired. Pacer™ is designed with a spiral textile reinforcement. UL 330 and CUL approved.

CONSTRUCTION TUBE: Nitrile synthetic rubber (ORS)

COVER: Chemivic™ synthetic rubber (ORS)

REINFORCEMENT: Spiral synthetic yarn with static wire

TEMPERATURE: -40 °F to 140 °F (-40 °C to 60 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Example: 3/4" Pacer™ Continental Contitech.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Gasoline Transfer
Style	Pacer Gasoline Lightweight Dispensing Hose
Construction Tube	Nitrile synthetic rubber (ORS)
Cover	Chemivic™ synthetic rubber (ORS)
Reinforcement	Spiral synthetic yarn with static wire
Color	Black
Min. Temperature	-40 °F

	-40 °C
Max. Temperature	140 °F 60 °C
Brand	PACER™
Packaging	Reel
Order Code	595-015

Specifications

I.D.	1 in 25.40 mm
Nom. O.D.	1.500 in 38.10 mm
Total Width	1.500 in 38.1 mm
Length	450.000 ft
Weight	0.600 lb/ft 0.89 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech