



Item # 20159304, ARCTIC ORTAC PLUS Air & Multipurpose Hose 3/4 in x 500 ft, 300 psi, Black

APPLICATION: A low-temperature hose construction for air, water, oil, kerosene, fuel oil and some chemical operations where temperatures fall as low as -65 °F (-54 °C).

CONSTRUCTION TUBE: Black low-temp, ECO oil-resistant synthetic rubber, RMA Class A (High Oil Resistance)

COVER: Black ultra-low temperature, ECO oil resistant synthetic rubber (with a blue stripe), RMA Class A (High Oil Resistance)

REINFORCEMENT: One textile braid

TEMPERATURE: -65 °F to 180 °F (-54 °C to 82 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Example: 9.5 mm 3/8" Arctic Ortac® Plus 2.1 MPA/300 psi Continental Contitech Made in the U.S.A.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Air and Multipurpose Transfer
Style	Air and Multipurpose Hose
Reinforcement	One textile braid
Cover	Black ultra-low temperature, ECO oil resistant synthetic rubber (with a blue stripe), RMA Class A (High Oil Resistance)
Construction Tube	Black low-temp, ECO oil-resistant synthetic rubber, RMA Class A (High Oil Resistance)

Color	Black
Min. Temperature	-65 °F -54 °C
Max. Temperature	180 °F 82 °C
Max. Working Pressure	300.0 psi 2.07 MPa
Packaging	Reel
Brand	ARCTIC ORTAC®
Order Code	536-275

Specifications

I.D.	3/4 in 19.10 mm
Nom. O.D.	1.180 in 30.00 mm
Length	500.000 ft
Weight	0.400 lb/ft 0.54 kg/m

MideastUS@contitech.us
 1-800-235-4632
Contitech.us

ContiTech