



## Item # 20457447, LPG DELIVERY PRO Dispense Hose MMOT 1 1/4 in x 1 ft, 350 PSI, Black

**APPLICATION:** LPG Delivery Pro™ is for residential and commercial delivery/transfer of liquid propane gas – the only UL listed LPG bobtail transfer assembly in the market. It features premium braided construction (1" ID and larger), excellent cold weather flexibility, a smooth cover for low drag resistance and low tube extraction to reduce contamination. **Not for LP appliances or other consumer applications.**

**CONSTRUCTION TUBE:** Nitrile

**COVER:** Synthetic rubber

**REINFORCEMENT:** 1/2" and 3/4" Textile spiral; 1" and 2" Textile braid

**TEMPERATURE:** -40 °F to 180 °F (-40 °C to 82 °C)

**COUPLINGS:** Factory installed crimped fittings only

**BRANDING:** Example: 1" (25.4 mm) Lpg Delivery Pro™ Cga Type 1 Lpg-Hose Issue No. E-8167 350 psi (2.4 MPa) Max WP. Made in USA.



[Product Specifications](#) | [Specifications](#)

### Product Specifications

<b>Reinforcement</b>	1/2" and 3/4" Textile spiral 1" and 2" Textile braid
<b>Cover</b>	Synthetic rubber
<b>Construction Tube</b>	Nitrile
<b>Color</b>	Black
<b>Max. Working Pressure</b>	350.0 psi 2.41 MPa

<b>Min. Temperature</b>	-40 °F -40 °C
<b>Max. Temperature</b>	180 °F 82 °C
<b>Brand</b>	LPG DELIVERY PRO™
<b>Order Code</b>	532-412

### Specifications

<b>End Type A</b>	Male NPTF
<b>End Type B</b>	Male NPTF
<b>I.D.</b>	1 1/4 in 31.80 mm
<b>Nom. O.D.</b>	1.800 in 45.70 mm
<b>Length</b>	1.000 ft
<b>Weight</b>	103.455 lb 0.680 lb/ft 1.01 kg/m

[MideastUS@contitech.us](mailto:MideastUS@contitech.us)

1-800-235-4632

Contitech.us

**ContiTech**