



Item # 20464771, LPG DELIVERY PRO Dispense Hose MMOT 1 1/2 in x 2 ft, 350 PSI, Black

APPLICATION: LPG Delivery Pro™ is for residential and commercial delivery/transfer of liquid propane gas – the only UL listed LPG bobtail transfer assembly in the market. It features premium braided construction (1" ID and larger), excellent cold weather flexibility, a smooth cover for low drag resistance and low tube extraction to reduce contamination. **Not for LP appliances or other consumer applications.**

CONSTRUCTION TUBE: Nitrile

COVER: Synthetic rubber

REINFORCEMENT: 1/2" and 3/4" Textile spiral; 1" and 2" Textile braid

TEMPERATURE: -40 °F to 180 °F (-40 °C to 82 °C)

COUPLINGS: Factory installed crimped fittings only

BRANDING: Example: 1" (25.4 mm) Lpg Delivery Pro™ Cga Type 1 Lpg-Hose Issue No. E-8167 350 psi (2.4 MPa) Max WP. Made in USA.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Reinforcement	1/2" and 3/4" Textile spiral 1" and 2" Textile braid
Cover	Synthetic rubber
Construction Tube	Nitrile
Color	Black
Max. Working Pressure	350.0 psi 2.41 MPa

Min. Temperature	-40 °F -40 °C
Max. Temperature	180 °F 82 °C
Brand	LPG DELIVERY PRO™
Order Code	532-412

Specifications

End Type A	Male NPTF
End Type B	Male NPTF
I.D.	1 1/2 in 38.10 mm
Nom. O.D.	2.080 in 52.80 mm
Length	2.000 ft
Weight	26.786 lb 1.100 lb/ft 1.64 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech