



Popular W-Series Hydraulic Assemblies



Quick-ship W assemblies help you meet tight deadlines and avoid lengthy made-to-order lead times.

THREE EASY STEPS TO CREATE YOUR ORDER Mix-and-Match

Combine your preferred assembly with a hydraulic filter and indicator to meet your performance requirements.

1. Choose the Assembly

Select the specific part numbers needed for both the head and the housing. Indicator ports are machined into every head.

2. Choose the Filter

Use the Donaldson Hydraulic Filtration Product Guide (F112100) as a reference guide for filter selection.

Refer to the filter choice tables found in the catalog to determine a specific part number to meet your performance, ISO cleanliness and pressure drop requirements.

The hydraulic catalog is available online at DonaldsonFilters.com.

3. Choose the Indicator

Indicators are optional but recommended to help monitor the condition of the filter and maintain the proper ISO cleanliness level for your application.



High-Performance DT Cartridge Filters

Donaldson DT filters provide superior hydraulic system protection.

Premium Uptime Protection

- Better protection from particles and contaminant
- Extends filter life with Donaldson DT Synteq™ media technology





W023 Spin-On Assembly



Donaldson Part Number	Port Size	Housing Length	Bypass Pressure Setting	Seal Material
Max Flow: 60 gpm (227 lpm) Max Pressure: 150 (1034 kPa) / 10.3 bar - Gray iron head construction - Excellent choice for use in high corrosion environments				
Head (includes head only)				
P574241	SAE-20 O-ring	NA	50 psi (345 kPa) / 3.45 bar	Buna-N
P575930	1-1/4" NPT	NA	None	Buna-N

WL15 In-Tank Assembly



Max Flow: 50 gpm (190 lpm) Max Pressure: 200 (1379 kPa) / 13.8 bar - Meets HF4 automotive standard - Optional secondary inlet port offers the use of a second return line				
Housing Assembly (includes head and bowl; does not include the 12" extension tube)				
P574231	(1) SAE-24 O-ring	9"	25 psi (172 kPa) / 1.72 bar	Buna-N
P575923	(1) SAE-24 O-ring	9"	50 psi (345 kPa) / 3.45 bar	Buna-N
P575924	(1) SAE-24 O-ring	9" with 12" extension	25 psi (172 kPa) / 1.72 bar	Buna-N
P575925	(2) 1½" SAE 4-Bolt Flange Code 61	9" with 12" extension	50 psi (345 kPa) / 3.45 bar	Buna-N

Head/Bowl/Housing Seal Kits		
Series	Part No.	Material
WL15/16	X011140	Buna
	X011141	Viton

WL16 In-Tank Assembly



Max Flow: 200 gpm (757 lpm)				
Max Pressure: 200 (1379 kPa) / 13.8 bar				
• Meets HF4 automotive standard				
• Top or side reservoir mounting options – with optional anti-flow back valve (side mounting only)				
Housing Assemblies (includes head and bowl)				
P574232	(2) SAE-24 O-ring	9"	25 psi (172 kPa) / 1.72 bar	Buna-N
P574233		18"		
P574234		27"		
P574235	(2) 1½" SAE 4-Bolt Flange Code 61	18"	50 psi (345 kPa) / 3.45 bar	
P574236	(1) 1½" SAE 4-Bolt Flange Code 61	18"		
P574237	(1) 1½" SAE 4-Bolt Flange Code 61	27"		
P575922	(2) SAE-24 O-ring	18"		



W061 In-Line Assembly



Donaldson Part Number	Port Size	Housing Length	Bypass Pressure Setting	Seal Material
Max Flow: 100 gpm (379 lpm) Max Pressure: 600 (4137 kPa) / 41.3 bar • Meets HF3 automotive standard • Cast iron head with steel housing construction • Bleed plug in head				
Heads (bowl ordered separately)				
P574242	SAE-12 O-ring	NA	50 psi (345 kPa) / 3.45 bar	Buna-N
P574243	SAE-16 O-ring			
P575929	SAE-16 O-ring		25 psi (172 kPa) / 1.72 bar	Viton
Housings (head ordered separately)				
X011115	NA	4"	NA	Buna-N
X011111		8"		
X011117		13"		

Filter Selection
Refer to page 110 of the Hydraulic Filtration Product Guide (F112100) for filter choices.

Head/Bowl/Housing Seal Kits

Series	Part No.	Material
W061	X011160	Buna
	X011161	Viton

W041 In-Line Assembly



Max Flow: 300 gpm (1136 lpm) Max Pressure: 500 (3450 kPa) / 34.5 bar - Base-mounted assembly - All aluminum head with plated steel housing and cast iron cover - Two drain plugs in base; bleed/fill plug in head				
Housing Assemblies (includes head and bowl)				
P574218	2" SAE 4-Bolt Flange Code 61	16"	50 psi (345 kPa) / 3.45 bar	Viton
P574219	2½" SAE 4-Bolt Flange Code 61	39"		
P575920	2" SAE 4-Bolt Flange Code 61	39"		
P575921	2½" SAE 4-Bolt Flange Code 61	16"		

Filter Selection
Refer to page 118 of the Hydraulic Filtration Product Guide (F112100) for filter choices.

Head/Bowl/Housing Seal Kits

Series	Part No.	Material
W041	X011156	Buna
	X011157	Viton



W451 In-Line Assembly



Donaldson Part Number	Port Size	Housing Length	Bypass Pressure Setting	Seal Material
Max Flow: 150 gpm (568 lpm) Max Pressure: 4500 (31027 kPa) / 310 bar • Meets HF4 automotive standard • Cast iron base and cover with bleed/fill plug • Steel cylinder with drain plug				
Housing Assemblies (includes head and bowl)				
P574220	SAE-24 O-ring	9"	50 psi (345 kPa) / 3.45 bar	Buna-N
P574221		18"		
P574222		27"		
P574223	1½" SAE 4-Bolt Flange Code 61	18"	90 psi (620 kPa) / 6.21 bar	
P574224		27"		
P574225		1½" SAE 4-Bolt Flange Code 62	18"	
P574226	Manifold Mount			
P574227				
P574228				
P574229				
P574230	SAE-24 O-ring	9"	NA	
P575915		18"		
P575916		27"		
P575917		9"		
P575918	1½" SAE 4-Bolt Flange Code 61	18"		90 psi (620 kPa) / 6.21 bar
P575919	9"			

Head/Bowl/Housing Seal Kits

Series	Part No.	Material
W451	X011174	Buna
	X011175	Viton

Filter Selection
Refer to page 168 of the Hydraulic Filtration Product Guide (F112100) for filter choices.

W620 In-Line Assembly



Max Flow: 150 gpm (568 lpm) Max Pressure: 6000 (41370 kPa) / 413.8 bar • Meets HF3 automotive standard • Cast iron head and steel housing				
Heads (bowl ordered separately)				
P574252	SAE-16 O-ring	NA	50 psi (345 kPa) / 3.45 bar	Buna-N
P574253	SAE-24 O-ring			
P574254	1½" SAE 4-Bolt Flange Code 62			
P575931	1¼" SAE 4-Bolt Flange Code 62		90 psi (620 kPa) / 6.21 bar	Viton
P575932			50 psi (345 kPa) / 3.45 bar	
P575933	SAE-16 O-ring		90 psi (620 kPa) / 6.21 bar	
P575934	SAE-20 O-ring		50 psi (345 kPa) / 3.45 bar	
P575935			90 psi (620 kPa) / 6.21 bar	
Housings (head ordered separately)				
X011557	NA	4"	NA	Buna-N
X011559		8"		
X011554		13"		
X011555		16"		

Head/Bowl/Housing Seal Kits

Series	Part No.	Material
W620	X011182	Buna
	X011183	Viton

Filter Selection
Refer to page 172 of the Hydraulic Filtration Product Guide (F112100) for filter choices.



Select an Indicator to Suit your Requirements

Select an indicator to help monitor the condition of the filter and maintain the proper ISO level for your application.

Electrical



Donaldson Part Number	Indicator Pressure Setting	Connector Style	Seal Material	Thermal Lockout	Surge Control
P572355	15 psi (103 kPa) /1.03 bar	Hirschmann	Buna-N	No	No
P572359	35 psi (241 kPa) /2.41 bar	Hirschmann	Buna-N	No	No
P572361	35 psi (241 kPa) /2.41 bar	Brad Harrison	Buna-N	No	No
P572369	70 psi (482 kPa) /4.83 bar	Hirschmann	Buna-N	No	No

Visual



P572345	15 psi (103 kPa) /1.03 bar	None	Buna-N	No	No
P572347	35 psi (241 kPa) /2.41 bar	None	Buna-N	No	No
P569636	35 psi (241 kPa) /2.41 bar	None	Viton	No	No
P572348	35 psi (241 kPa) /2.41 bar	None	Buna-N	Yes	Yes
P567456	35 psi (241 kPa) /2.41 bar	None	Viton	Yes	Yes
P572319	70 psi (482 kPa) /4.83 bar	None	Buna-N	Yes	Yes
P567457	70 psi (482 kPa) /4.83 bar	None	Viton	Yes	Yes
P569637	70 psi (482 kPa) /4.83 bar	None	Viton	No	No
P572353	100 psi (689 kPa) /6.89 bar	None	Buna-N	Yes	Yes
P572354	100 psi (689 kPa) /6.89 bar	None	Viton	Yes	Yes

Brad Harrison® is a registered trademark of Woodhead Industries, Inc.

Hirschmann® is a registered trademark of Richard Hirschmann of America Inc.

Buna-N® and Viton® are registered trademarks of E. I. DuPont de Nemours and Co.



Visual / Electrical



Donaldson Part Number	Indicator Pressure Setting	Connector Style	Seal Material	Thermal Lockout	Surge Control
P572323	15 psi (103 kPa) /1.03 bar	Hirschmann	Buna-N	No	No
P572342	15 psi (103 kPa) /1.03 bar	3-wire flying leads	Buna-N	No	No
P572327	35 psi (241 kPa) /2.41 bar	Hirschmann	Buna-N	No	No
P572329	35 psi (241 kPa) /2.41 bar	Brad Harrison	Buna-N	No	No
P569638	35 psi (241 kPa) /2.41 bar	Hirschmann	Viton	Yes	No
P572384	35 psi (241 kPa) /2.41 bar	Hirschmann	Buna-N	Yes	Yes
P567458	35 psi (241 kPa) /2.41 bar	Hirschmann	Viton	Yes	Yes
P572385	35 psi (241 kPa) /2.41 bar	Brad Harrison	Buna-N	Yes	Yes
P572349	35 psi (241 kPa) /2.41 bar	3-wire flying leads	Buna-N	No	No
P572320	70 psi (482 kPa) /4.83 bar	Hirschmann	Buna-N	Yes	Yes
P567459	70 psi (482 kPa) /4.83 bar	Brad Harrison	Buna-N	Yes	Yes
P572373	70 psi (482 kPa) /4.83 bar	Hirschmann	Buna-N	Yes	No
P569639	70 psi (482 kPa) /4.83 bar	Hirschmann	Viton	Yes	No
P572387	100 psi (689 kPa) /6.89 bar	Hirschmann	Buna-N	Yes	Yes

Electrical

X011061	18 psi (124 kPa) /1.24 bar	Hirschmann	Buna-N	No	No
X011064	35 psi (241 kPa) /2.41 bar	Hirschmann	Buna-N	No	No
X011065	18 psi (124 kPa) /1.24 bar	Brad Harrison	Buna-N	No	No
X011066	35 psi (241 kPa) /2.41 bar	Brad Harrison	Buna-N	No	No

Pressure Gauge

X011059	25 psi (172 kPa) /1.72 bar
X011060	50 psi (345 kPa) /3.45 bar



How to Select a Filter for your W Assembly

Use the **Hydraulic Filtration Product Guide (F112100)** as a reference tool.

Refer to the filter choice tables found in the hydraulic catalog to determine a specific part number that will meet your performance, ISO cleanliness and pressure drop requirements.

High-Performance DT Filters Provide Superior System Protection

Premium Uptime Protection


Every hydraulic system has suspended particles in its fluid. Contaminants grind and wear at the surface of moving parts, introducing even more particles into the system. These contaminants cause more than 70% of all hydraulic system downtime.

Donaldson high-performance DT cartridge filters provide better protection from the particles and contaminants that reduce the effectiveness of lubricant and hydraulic fluid. Using Donaldson DT Synteq™ media technology, these filters extend filter life, allow higher initial cleanliness and provide superior system protection.




Donaldson DT filters are stocked and ready to ship!

Dirt-Holding Capacity Improvement



Pressure Drop Improvement



Donaldson.
FILTRATION SOLUTIONS

Donaldson Company, Inc.
Minneapolis, MN

donaldsonfilters.com
donaldson.com
catalog.donaldson.com

North America 800-374-1374
Mexico +52-449-910-6150
Latin America and Caribbean +52-449-910-6150

Brochure No. F111410 ENG (8/16)
© 2016 Donaldson Company, Inc. All rights reserved.
Donaldson Company, Inc. reserves the right to change or discontinue any model or specification at any time and without notice.
Printed in the U.S.A.