Eaton ADE6M252SSS

Catalog Number: ADE6M252SSS

Eaton ADE 6F, Armoured, Stainless Steel, M25, 2 (M), 12-21

General specifications

Product Name

Eaton Capri ADE-6F Cable Gland for

Hazardous Area

ADE6M252SSS

Catalog Number

EAN

3589350067637

Product Length/Depth

75.5 mm

Product Height

Product Weight

33 mm

Product Width

. . .

30 mm 146.4 g

Warranty

Compliances

No warranty Contact Manufacturer

Multiple listings- contact manufacturer



Product specifications

Sealing type

Silicone

Connector type

Straight

Type of sealing

Diaphragm

Gland type

Armoured

Protection, proofing and resistance

Shock Resistant

Nominal thread size Metric/PG

25

Gland size

7

Material quality

Stainless steel V4A

For ex-zone gas

1, 2

Version

Explosion - Tested

Pitch thread

1.5 mm

For ex-zone dust

21, 22

Working temperature - min

-30 °C

Suitable for cable diameter - min

12 mm

Outer sheath (min/max)

12-21

Degree of protection (IP)

IP68

Cable sealing range

2 (M)

Thread Size

Resources

Technical data sheets

ADE-6F Datasheet

| | Ν | 1: | 2 | 5 |
|---|---|----|---|---|
| ш | | 14 | _ | v |

Color

Natural colour

Material

Stainless steel

Metal

Lamp type included

Halogen Free

Working temperature - max

80 °C

Protection type

Flameproof and increased safety

Suitable for cable diameter - max

21 mm

Hexagon angular dimension

33 mm

Surface protection

Untreated

Model

Straight

Thread Length

15 mm

Thread type

Metric

Wrench width

30 mm



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia