

Eaton CPS14 20

Catalog Number: CPS14 20

Eaton Crouse-Hinds series Arktite CPS receptacle assembly, 20A, Dead end, Two-wire, three-pole, Brass contacts, 60-400 Hz, 1 HP, Copper-free aluminum, Spring door, Factory sealed, 3/4", Delayed action circuit breaking, 125-250 Vac/18 Vdc

General specifications

Product Name	Catalog Number
Eaton Crouse-Hinds series Arktite CPS receptacle assembly	CPS14 20
	UPC
	782274178707
Product Length/Depth	Product Height
3 in	4.81 in
Product Width	Product Weight
3.5 in	3.85 lb

Certifications and compliances

Area classification

Hazardous/Classified Locations

Standards type

NEC/CEC

NEC hazardous rating

Class I, Division 1

Class I, Division 2

Product specifications

Amperage Rating

20A

Configuration

Two-wire, three-pole

Back box style

Dead end

Trade size

3/4"

Receptacle style

Spring door

Voltage rating

125-250 Vac/18 Vdc

Horsepower

1 hp

Frequency rating

60-400 Hz

Material

Copper-free aluminum

Contact material

Brass

Special features

Factory sealed

Type

Delayed action circuit breaking

Resources

Catalogs

[Arktite CPS, CPP and CPR Explosionproof Receptacles and Plugs catalog page](#)

Certification reports

[Arktite CPS, CPP, CPR Explosionproof Receptacles, Plugs and Connectors UL certification](#)

[Arktite CPS, CPP, CPR Explosionproof Receptacles, Plugs and Connectors Canadian certification](#)

Installation instructions

IF 1424 - DSD, GFS, CPS and ENR Replacement Covers

IF 654 - CPS 20A Receptacles

IF 165 - CPS Receptacles

Specifications and datasheets

Eaton Specification Sheet - CPS14 20



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)