Product specifications

Eaton ADE6CM252SSSCN

Catalog Number: ADE6CM252SSSCN

Eaton ADE 6FC, Armoured Barrier, Stainless Steel, M25, 2 (M), 12-21

General specifications

Product Name Eaton Capri ADE-6FC Cable Gland for Hazardous Area	**Catalog Number** ADE6CM252SSSCN
	EAN 3589350037012
Product Length/Depth 75.5 mm	**Product Height** 33 mm
Product Width 30 mm	**Product Weight** 230.258 g
Warranty No warranty	**Compliances** Contact Manufacturer Multiple listings- contact manufacturer

Powering Business Worldwide

Product specifications

Sealing type
Silicone

Connector type
Straight

Type of sealing
Diaphragm

Gland type
Armoured Barrier

Protection, proofing and resistance
Shock Resistant

Nominal thread size Metric/PG
25

Suitable for
Armoured Cable

Gland size
7

Material quality
Stainless steel V4A

For ex-zone gas
1, 2

Fitted with:
Strain Relief
Separable Screw Gland

Version
Explosion - Tested
EMC

Pitch thread
1.5 mm

For ex-zone dust
21, 22

Working temperature - min
-60 °C

Suitable for cable diameter - min
12 mm

Outer sheath (min/max)
12-21

Resources

Technical data sheets
ADE-6FC Datasheet

Degree of protection (IP)

IP66

Cable sealing range

2 (M)

Thread Size

M25

Color

Natural colour

Material

Metal

Stainless steel

Lamp type included

Halogen Free

Working temperature - max

80 °C

Protection type

Flameproof and increased safety

Suitable for cable diameter - max

21 mm

Hexagon angular dimension

33 mm

Surface protection

Untreated

Integrated function

Screened

Model

Straight

Thread Length

15 mm

Thread type

Metric

Barrier type

TSC Compound

Wrench width

30 mm

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia