

Eaton ADE6CM403SSSCN

Catalog Number: ADE6CM403SSSCN

Eaton ADE 6FC, Armoured Barrier, Stainless Steel, M40, 3 (L), 27-41

General specifications

Product Name	Catalog Number
Eaton Capri ADE-6FC Cable Gland for Hazardous Area	ADE6CM403SSSCN
	EAN
	3589350037104
Product Length/Depth	Product Height
107 mm	60.5 mm
Product Width	Product Weight
55 mm	730.77 g
Warranty	Compliances
No warranty	Contact Manufacturer
	Multiple listings- contact manufacturer

Product specifications

Sealing type

Silicone

Connector type

Straight

Type of sealing

Diaphragm

Gland type

Armoured Barrier

Protection, proofing and resistance

Shock Resistant

Nominal thread size Metric/PG

40

Suitable for

Armoured Cable

Gland size

10

Material quality

Stainless steel V4A

For ex-zone gas

1, 2

Fitted with:

Strain Relief

Separable Screw Gland

Version

Explosion - Tested

EMC

Pitch thread

1.5 mm

For ex-zone dust

21, 22

Working temperature - min

-60 °C

Suitable for cable diameter - min

27 mm

Outer sheath (min/max)

27-41

Resources

Technical data sheets

[ADE-6FC Datasheet](#)

Degree of protection (IP)

IP66

Cable sealing range

3 (L)

Thread Size

M40

Color

Natural colour

Material

Stainless steel

Metal

Lamp type included

Halogen Free

Working temperature - max

80 °C

Protection type

Flameproof and increased safety

Suitable for cable diameter - max

41 mm

Hexagon angular dimension

60.5 mm

Surface protection

Untreated

Integrated function

Screened

Model

Straight

Thread Length

15 mm

Thread type

Metric

Barrier type

TSC Compound

Wrench width

55 mm



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)