Eaton EDS2130 SA

Catalog Number: EDS2130 SA

Eaton Crouse-Hinds series EDS snap switch control station, 20A, With switch, With one 3/4" hub, Copper-free aluminum, 1, Singlegang, Three-pole, 2, 120-277V, Dead end, 3-way, 3/4", 120-277 Vac



General specifications

Product Name

Eaton Crouse-Hinds series EDS snap

switch control station

UPC

782274533971

Product Weight

Catalog Number

EDS2130 SA

Product Length/Depth

5.06 in

Product Height

5.875 in

Product Width

3.7 lb

3.5 in 3.7

Photo is representative



Certifications and compliances

Area classification

Hazardous/Classified Locations

Standards type

NEC/CEC

NEC hazardous rating

Class I, Division 1

Class I, Division 2

Class II, Division 1

Class II, Division 2

Class III

NEMA Rating

3

7

9

Product specifications

Enclosure type

With switch

Trade size

3/4"

Number Of Poles

Three-pole

Switch function

3-way

Number of gangs

Single-gang

Style

Dead end

Voltage rating

120-277 Vac

Amperage Rating

20A

Hub style

With one 3/4" hub

Number of devices

1

Number of pushbuttons

2

Primary voltage range

120-277V

Material

Copper-free aluminum

Resources

Catalogs

EDS and EDSX Fully Assembled Snap Switches catalog page

Certification reports

EDS and EFD Explosionproof Snap Switches UL certification - industrial control panels and assemblies

EDS and EFD Explosionproof Snap Switches Canadian certification - snap

switches

EDS and EFD Explosionproof Snap Switches Canadian certification industrial control panels and assemblies

EDS and EFD Explosionproof Snap Switches UL certification - snap switches

Installation instructions

IF 328 - EDS, EFS, EDSC and EFSC Single- and Two-gang Device Bodies

IF 242 - EDS and EDSC Control Stations

Specifications and datasheets

Eaton Specification Sheet - EDS2130 SA



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia