

# Vaporproof lighting

## Features:

- Durable die cast housing and guard for long product life
- Powder paint finish for corrosive environments
- Available in pendant, box and wall mounts
- Fixtures may be purchased complete or as components
- Fixtures constructed of die cast aluminum; screw-on guards are zinc die cast
- Heat-resistant clear globe available on 100 watt series
- Wire guard available

## Certifications and compliances:

- UL1598
- UL Listed File No. E-15625
- cUL Standard CSA C22.2 No 250.0
- Suitable for wet locations
- 100W max. incandescent series is UL approved for 27W max. SBCFL (equivalent to 100W incandescent)
- 200W max. incandescent series is UL approved for 42W max. SBCFL (equivalent to 200W incandescent)

Clear glass is standard; colors are available; plastic (polycarbonate) globes, which are virtually unbreakable, are available in colors and are used as an alternative to glass globe/guard combinations (not recommended to exceed 60 watts).

## VAPORPROOF FIXTURES – GASKETED, CORROSION-RESISTANT DIE CAST CONSTRUCTION, GLASS GLOBES, DIE CAST GUARDS, UL LISTED



TP7600,  
TP7601



TP7800,  
TP7801,  
TP7860



TP7610,  
TP7611,  
TP7805



TP7620,  
TP7621



TP7810,  
TP7811



TP7630,  
TP7815



TP7640



TP7820



TP7650,  
TP7825

| Cat. #                                             | Description                         | Hole size | Incandescent watts | SBCFL watts | Std. unit carton | Wt. lbs. per 100 |
|----------------------------------------------------|-------------------------------------|-----------|--------------------|-------------|------------------|------------------|
| <b>4" box mounted</b>                              |                                     |           |                    |             |                  |                  |
| TP7600 <sup>W</sup>                                | Clear globe, cast guard             | 1/2"      | 100                | 27          | 1                | 325.0            |
| TP7601                                             | Clear globe, cast guard             | 3/4"      | 100                | 27          | 1                | 324.0            |
| TP7800                                             | Clear globe, wire guard             | 1/2"      | 200                | 42          | 1                | 516.7            |
| TP7801                                             | Clear globe, wire guard             | 3/4"      | 200                | 42          | 1                | 516.0            |
| TP7860                                             | Fluorescent clear globe, wire guard | 1/2"      | 13                 | -           | 1                | 413.0            |
| TP7610                                             | Clear globe                         | 1/2"      | 100                | 27          | 1                | 258.3            |
| TP7611                                             | Clear globe                         | 3/4"      | 100                | 27          | 1                | 258.0            |
| TP7805                                             | Clear globe                         | 1/2"      | 200                | 42          | 1                | 283.3            |
| <b>Pendant mount</b>                               |                                     |           |                    |             |                  |                  |
| TP7620                                             | Clear globe, cast guard             | 1/2"      | 100                | 27          | 1                | 300.0            |
| TP7621                                             | Clear globe, cast guard             | 3/4"      | 100                | 27          | 1                | 299.0            |
| TP7810                                             | Clear globe, wire guard             | 1/2"      | 200                | 42          | 1                | 350.0            |
| TP7811                                             | Clear globe, wire guard             | 3/4"      | 200                | 42          | 1                | 349.0            |
| TP7630                                             | Clear globe                         | 1/2"      | 100                | 27          | 1                | 208.4            |
| TP7815                                             | Clear globe                         | 1/2"      | 200                | 42          | 1                | 258.4            |
| <b>Surface mount, fits 3" &amp; 4" round boxes</b> |                                     |           |                    |             |                  |                  |
| TP7640                                             | Clear globe, cast guard             | -         | 100                | 27          | 1                | 275.0            |
| TP7820                                             | Clear globe, wire guard             | -         | 200                | 42          | 1                | 333.3            |
| TP7650                                             | Clear globe                         | -         | 100                | 27          | 1                | 216.7            |
| TP7825                                             | Clear globe                         | -         | 200                | 42          | 1                | 180.0            |

<sup>W</sup> Suitable for base-up applications.

# Vaporproof lighting



TP7670, TP7835



TP7845

| Cat. #                              | Description             | Incandescent watts | SBCFL watts | Std. unit carton | Wt. lbs. per 100 |
|-------------------------------------|-------------------------|--------------------|-------------|------------------|------------------|
| <b>Right angle bracket fixtures</b> |                         |                    |             |                  |                  |
| TP7660                              | Clear globe, cast guard | 100                | 27          | 1                | 300.0            |
| TP7830                              | Clear globe, wire guard | 200                | 42          | 1                | 516.7            |
| TP7670                              | Clear globe             | 100                | 27          | 1                | 200.0            |
| TP7835                              | Clear globe             | 200                | 42          | 1                | 400.0            |
| <b>Box mounted</b>                  |                         |                    |             |                  |                  |
| TP7680                              | Clear globe, cast guard | 100                | 27          | 1                | 350.0            |
| TP7840                              | Clear globe, wire guard | 200                | 42          | 1                | 560.0            |
| TP7845                              | Clear globe             | 200                | 42          | 1                | 450.0            |

## VAPORPROOF COMPONENTS




Pendant



Ceiling box cap



Ceiling box



Right angle



Right angle/box

| Cat. #                                                                | Description | Incandescent watts | SBCFL watts | Std. unit carton | Wt. lbs. per 100 |
|-----------------------------------------------------------------------|-------------|--------------------|-------------|------------------|------------------|
| <b>Pendant cap, porcelain socket, gasket &amp; screws</b>             |             |                    |             |                  |                  |
| TP7496                                                                | Gray, 1/2"  | 100                | 27          | 10               | 18               |
| TP7497                                                                | Gray, 3/4"  | 100                | 27          | 10               | 18               |
| TP7498                                                                | Gray, 1/2"  | 200                | 42          | 10               | 10               |
| TP7499                                                                | Gray, 3/4"  | 200                | 42          | 10               | 10               |
| <b>Ceiling box cap, socket, gasket &amp; screws</b>                   |             |                    |             |                  |                  |
| TP7447                                                                | Gray        | 100                | 27          | 10               | 12               |
| TP7479                                                                | Gray        | 200                | 42          | 10               | 12               |
| <b>Ceiling mount box with gaskets, porcelain socket &amp; screws</b>  |             |                    |             |                  |                  |
| TP7450                                                                | Gray, 1/2"  | 100                | 27          | 10               | 19               |
| TP7478                                                                | Gray, 3/4"  | 100                | 27          | 10               | 19               |
| TP7451                                                                | Gray, 1/2"  | 200                | 42          | 10               | 19               |
| TP7479                                                                | Gray, 3/4"  | 200                | 42          | 10               | 19               |
| <b>Right angle bracket, gasket, socket &amp; screws</b>               |             |                    |             |                  |                  |
| TP7445                                                                | Gray        | 100                | 27          | 10               | 21               |
| TP7446                                                                | Gray        | 200                | 42          | 6                | 12               |
| <b>Right angle bracket, attached box, gasket, socket &amp; screws</b> |             |                    |             |                  |                  |
| TP7440                                                                | Gray, 1/2"  | 100                | 27          | 1                | 3                |

Vaporproof

# Vaporproof lighting

## VAPORPROOF FIXTURE ACCESSORIES



TP7460 - TP7466




TP7468 - TP7472



TP7474, TP7475









TP7476



TP7477

| Cat. # | Description                   | Incandescent watts | SBCFL watts | Std. unit carton | Wt. lbs. per 100 |
|--------|-------------------------------|--------------------|-------------|------------------|------------------|
| TP7460 | Glass clear globe, 130°F max. | 100                | 27          | 12               | 98.0             |
| TP7462 | Glass amber globe             | 100                | 27          | 12               | 120.0            |
| TP7463 | Glass blue globe              | 100                | 27          | 12               | 120.0            |
| TP7464 | Glass green globe             | 100                | 27          | 12               | 120.0            |
| TP7466 | Glass clear globe             | 200                | 42          | 6                | 200.0            |
| TP7468 | Lexan clear prismatic         | 75                 | -           | 12               | 58.4             |
| TP7469 | Lexan blue prismatic          | 60                 | -           | 12               | 58.4             |
| TP7470 | Lexan red prismatic           | 75                 | -           | 12               | 58.4             |
| TP7471 | Lexan amber prismatic         | 75                 | -           | 12               | 58.4             |
| TP7472 | Lexan white                   | 75                 | -           | 12               | 58.4             |
| TP7474 | Bayonet mount die cast guard  | 100                | 27          | 12               | 108.4            |
| TP7475 | Wire guard                    | 200                | 42          | 6                | 183.4            |
| TP7476 | Clamp-on wire guard           | 100                | 27          | 12               | 62.5             |
| TP7477 | Adapter plate                 | -                  | -           | 12               | 62.5             |

## Dimensions (100 watt):



## Dimensions (200 watt):

| Cat. # | Length  | Overall width | Depth  |
|--------|---------|---------------|--------|
| TP7830 | 12 1/2" | 5 1/2"        | 6 7/8" |
| TP7840 | 12 1/2" | 5 1/2"        | 8"     |
| TP7820 | 7 1/2"  | 4 1/2"        | -      |
| TP7810 | 11 1/2" | 5 1/2"        | -      |
| TP7800 | 10 3/4" | 5 1/2"        | -      |

## PHOTOELECTRIC LIGHTING CONTROLS



TP7925



TP7927

### Applications:

- Used for sunset activated automatic control of night lighting
- May be used to control outdoor lighting and signs

### Features:

- Durable, weatherproof construction
- Built-in time delay prevents operation triggered by temporary light flashes

| Cat. # | Description                  | Std. unit<br>pkg. | Wt. lbs.<br>per 100 |
|--------|------------------------------|-------------------|---------------------|
| TP7925 | 1200W swivel photocell, 120V | 10                | 8.3                 |
| TP7927 | 300W photocell, 120V         | 10                | 8.3                 |