

# Eaton ADE1M202SSN

Catalog Number: ADE1M202SSN

Eaton ADE 1F2, Non-armoured, Stainless Steel, M20, 2 (M), 7-12



Photo is representative

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Capri ADE-1F2 Cable Gland for Hazardous Area	ADE1M202SSN
	<b>EAN</b>
	3589350032475
<b>Product Length/Depth</b>	<b>Product Height</b>
42 mm	26.4 mm
<b>Product Width</b>	<b>Product Weight</b>
24 mm	51.2 g

## Compliances

Contact Manufacturer

Multiple listings- contact manufacturer

## defaultTaxonomyAttributeLabel

### Material

#### Metal

Stainless steel

### Cable sealing range

2 (M)

### Color

Natural colour

### Connector type

Straight

### Gland size

5

### Gland type

Non-armoured

### Outer sheath (min/max)

7-12

### Protection type

Flameproof and increased safety

### Sealing type

Silicone

### Thread Size

M20

### Nominal thread size Metric/PG

25

### Pitch thread

1.5 mm

### Thread Length

15 mm

### Wrench width

19 mm

### Hexagon angular dimension

20.9 mm

### Suitable for cable diameter - max

12 mm

### Suitable for cable diameter - min

7 mm

## Resources

### Technical data sheets

[ADE-1F2 Datasheet](#)

Material quality

Stainless steel V4A

Surface protection

Untreated

Degree of protection (IP)

IP68

Model

Straight

Type of sealing

Sealing ring

Working temperature - max

140 °C

Working temperature - min

-60 °C

For ex-zone gas

1, 2

For ex-zone dust

21, 22

Lamp type included

Halogen Free

Thread type

Metric

Protection, proofing and resistance

Shock Resistant

Version

Explosion - Tested