

Tender Text



Product photo could vary from the actual product

Product No.: [5010011](#)

25S20-11

Multi-stage submersible pump for raw water supply, groundwater lowering and pressure boosting. The pump is suitable for pumping clean, thin, non-aggressive liquids without solid particles or fibers.

The pump is made entirely of Stainless steel DIN W.-Nr. DIN W.-Nr. 1.4301 and suitable for horizontal and vertical installation.

The pump is fitted with a built-in non-return valve.

Liquid:

Pumped liquid: Water
Maximum liquid temperature: 104 °F
Liquid temperature during operation: 68 °F
Density: 62.29 lb/ft³

Technical:

Speed for pump data: 3450 rpm
Actual calculated flow: 24 US gpm
Resulting head of the pump: 229.1 ft
Curve tolerance: ISO9906:2012 3B

Materials:

Pump: Stainless steel
DIN W.-Nr. 1.4301
AISI 304
Impeller: Stainless steel
DIN W.-Nr. 1.4301
AISI 304

Installation:


Pump outlet: 1 1/2"NPT
Motor diameter: 4 inch

Electrical data:


Power (P2) required by pump: 2.333 HP

Others:




Net weight: 8.38 lb
Gross weight: 12.3 lb

Position	Count	Description
	1	<p>25S20-11</p>  <p>Product photo could vary from the actual product</p> <p>Product No.: 5010011</p> <p>Multi-stage submersible pump for raw water supply, groundwater lowering and pressure boosting. The pump is suitable for pumping clean, thin, non-aggressive liquids without solid particles or fibers.</p> <p>The pump is made entirely of Stainless steel DIN W.-Nr. DIN W.-Nr. 1.4301 and suitable for horizontal and vertical installation. The pump is fitted with a built-in non-return valve.</p> <p>Liquid:</p> <p>Pumped liquid: Water</p> <p>Maximum liquid temperature: 104 °F</p> <p>Liquid temperature during operation: 68 °F</p> <p>Density: 62.29 lb/ft³</p> <p>Technical:</p> <p>Speed for pump data: 3450 rpm</p> <p>Actual calculated flow: 24 US gpm</p> <p>Resulting head of the pump: 229.1 ft</p> <p>Curve tolerance: ISO9906:2012 3B</p> <p>Materials:</p> <p>Pump: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p> <p>Impeller: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p> <p>Installation:</p> <p>Pump outlet: 1 1/2"NPT</p> <p>Motor diameter: 4 inch</p> <p>Electrical data:</p> <p>Power (P2) required by pump: 2.333 HP</p> <p>Others:</p> <p>Net weight: 8.38 lb</p> <p>Gross weight: 12.3 lb</p>


5010011 25S20-11 60 Hz



Description	Value
General information:	
Product name:	25S20-11
Product No.:	5010011
EAN:	5700390229719
Technical:	
Speed for pump data:	3450 rpm
Actual calculated flow:	24 US gpm
Resulting head of the pump:	229.1 ft
Stages:	11
Curve tolerance:	ISO9906:2012 3B
Model:	A
Valve:	pump with built-in non-return valve
Materials:	
Pump:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Impeller:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Installation:	
Pump outlet:	1 1/2"NPT
Motor diameter:	4 inch
Liquid:	
Pumped liquid:	Water
Maximum liquid temperature:	104 °F
Liquid temperature during operation:	68 °F
Density:	62.29 lb/ft³
Electrical data:	
Applic. motor:	NEMA
Power (P2) required by pump:	2.333 HP
Others:	
Net weight:	8.38 lb
Gross weight:	12.3 lb
Sales region:	Namreg



5010011 25S20-11 60 Hz



Note! All units are in [mm] unless otherwise stated.
Disclaimer: This simplified dimensional drawing does not show all details.



Company name:

Created by:

Phone:

Date:

2/22/2018

Order Data:


Product name: 25S20-11

Amount: 1

Product No.: 5010011


Total: Price on request

Exploded view (tm019315 1600)



TM019315

Sectional drawing (tm019325 1600)



TM019325

Parts list 25S20-11, Prod number 5010011

Valid from 1.8.1994 (9432)

Position	Description	Annotation	Classification data	Part No.	Count	Unit
	Nut				1	pcs
	Impeller				11	pcs
	Washer				1	pcs
- 1	Valve casing cpl.				1	pcs
	Valve casing				1	
	Bearing, top				1	
2	Valve cone				1	
3	Valve seat				1	
70	Valve guide				1	
1b	Distance piece				1	pcs
- 9	Chamber				10	pcs
	Chamber w/o guide vanes				1	
	Bearing				1	
7	Neck ring				1	
- 10	Chamber, bottom				1	pcs
	Chamber w/o guide vanes				1	
7	Neck ring				1	
14	Suction interconnector				1	pcs
16	Shaft cpl.		Length: 287,5		1	pcs
17	Strap		Length: 296		3	pcs
18	Cable guard				1	pcs
18a	Pan head screw				2	pcs
19	Screw w/washer				3	pcs
64	Priming disc				1	pcs
76	Nameplate				1	pcs