



## PRODUCT NUMBER: LA258G Nitri Guard Plus - LA258G

Mechanical and chemical resistance to a large range of products (oils, detergents and many solvents). Preparation of greasy products, production of paints, varnishes.

# Honeywell

### Overview

**Reference Number**

LA258G

**Product Type**

Gloves

**Range**

Chemical Protection

**Line**

Heavy chemical

**Brand**

Honeywell

**Brand formerly known as**

NORTH

**Industry**

- Agriculture
- Automotive and Part Manufacturer
- Chemical Industries
- Food Industries
- Industrial Cleaning
- Laboratory
- Petro-chemical
- Water treatment

**Product Use**

Mechanical and chemical resistance to a large range of products (oils, detergents and many solvents). Preparation of greasy products, production of paints, varnishes.

### Features & Benefits

**Feature**

Unsupported nitrile glove. Sanitized interior. Raised pattern. Thickness : 0.63 mm. Length : 45 cm.

**Benefit**

**COMFORT** Its nitrile formula has been selected to give the glove greater elasticity and unrivalled dexterity. The Sanitized interior facilitates the introduction and removal of the glove. The glove's rough finish improves the grip, to grasp objects in a greasy or damp atmosphere. Gloves will not swell, sag or weaken from fat absorption. Curved shaped hand provides a natural fit. **RESISTANCE** Nitrile ensures good chemical properties and excellent mechanical characteristics (abrasion). It is particularly suitable for the handling of oils, greases and hydrocarbons. Outperforms natural rubber, neoprene and vinyl gloves when exposed to solvents, caustics and animal fats. Avoid contact with solvents containing ketones.

SAFETY Category III glove for constant quality. The cuff helps to protect a large part of the forearm. HYGIENE Gloves are free of latex proteins which can cause allergic reactions

## Technical Description

### Description

Unsupported nitrile glove. Sanitized interior. Raised pattern. Thickness : 0.63 mm. Length : 45 cm.

### Product Technology

Dipped

### Glove/liner color

Green

### Coating Type

Nitrile

### Length

45 cm

### Thickness

0,63 mm

### Harmlessness

In conformity with the European standards.

### Dexterity

Class 5

### Sizes

7S, 8M, 9L, 10XL, 11XXL

## EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	3
Cutting resistance (Coupe test)	0
Tear resistance	0
Puncture resistance	2

## EN 374-3 Resistance to

Resistance to permeation by chemicals	JKL
---------------------------------------	-----

## Packaging Label

### Tagging

CE0075 Honeywell LA258G XX EN 420 EN 388 : 3002 EN 374-3 : JKL

## Certifications

### EC Category PPE

3

### EC Certificate Number

0075/797/162/08/13/0760 EXT 03/08/13

### EC Attestation

EC Attestation

### EC Attestation Number

0075/797/162/08/13/0760 EXT 03/08/13

### Certifications

- EN 0075/797/162/08/13/0760 EXT 03/08/13

## Additional Information

### User Manual

UI 104

## Maintenance

### Storage Information

Minimum packaging : 12 pairs. Cartons of 72 pairs.

### Care Instructions

In order to keep its properties, this article should not be cleaned.