

**PRODUCT NUMBER: KV18A-100****Perfect Fit Aramid -****KV18A-100**

7 gauge, standard weight, 100% Kevlar seamless knit glove.

Overview

Reference Number

KV18A-100

Product Type

Gloves

Range

specificprotection

Line

Cut resistant

Brand

Sperian

Brand formerly known as

PERFECT FIT

Industry

- Automotive and Part Manufacturer
- Building and Construction
- Fishing
- General Industry
- Glass Industries
- Metal steel
- Minning and Quarrying
- Ship Building
- Wood Industries

Product Use

Sheet Metal • Glass Handling • Canning • Automotive Sub-Assembly • Metal Stamping

Features & Benefits

Feature

100% Kevlar

Benefit

Kevlar is 5x stronger than steel on an equal weight basis, and can withstand temperatures up to 900°F (480° C) without melting or degrading.

Feature

Seamless knit

Benefit

Seamless knit gloves have no seams to rub and chafe.

Technical Description

Description

100% Kevlar seamless knit glove offers excellent cut and abrasion protection.

Product Technology

DuPont™ Kevlar® engineered fiber

Fiber

100% Kevlar®

Gauge

7 gauge

Glove/liner color

Yellow

Weight (in grams)

Standard weight

Sizes

Men's, Ladies' (KV18AL-100), Jumbo (KV18AJ-100), and Youth (KV18AY-100)

EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	1
---------------------	---

ASTM D3389-05

ANSI Level Abrasion Resistance	Level 1
--------------------------------	---------

ASTM F1790-97

ANSI Level Cut Resistance	Level 3
---------------------------	---------

Packaging Label

UOM

Pair

Certifications

Quality Assurance

ISO 9001 / 2000

Photos & Images

Prod Image_KV18A-100

<http://www.honeywellsafety.com/assets/0/324/980/987/b6a3492a-d352-47db-9458-545655a41913.jpg>

Maintenance

Care Instructions

Dry cleaning is the acceptable cleaning method for gloves of KEVLAR fiber. Some differences in shrinkage, weight loss, yarn tensile strength, and color related to staining or the cleaning method may be seen, but there is no significant impact on cut resistance up to 30 cleaning cycles (without industrial use between cycles). Thirty cleaning cycles is considered to be more than can be expected because of normal wear. Chlorine bleach is not recommended for KEVLAR - chlorine will cause rapid degradation of the fiber. Wash or dry temperatures should not exceed 170° F.

WARNING : Laundering gloves that have been in contact with toxic or corrosive chemicals may result in a chemical reaction, including fumes that could cause personal injury, serious illness or death.

Packaging

Packaging Specs Case Box

144

Unit of Measure

Pair

Quantity per Box/Pack/Case

144

Quantity per Carton

144

Quantity for Minimum Order

144

Country of Origin

China

© Honeywell International Inc.