

Compression Splice Reducer

By Burndy Catalog # Y3129R

350 kcmil CU Long Barrel Size Reduced Down To 250 kcmil Wire Size, Internal Chamfer, Tin Plated, Up to 35kV, RED Color Code, 18 or 324 Die Index.



Application

Wire Reducing Splice Adapter Insert

General

Catalog Number Y3129R Color Code Red

Connector Type LONG BARREL

Die Index 18
EU ROHS Indicator Yes
Feature - Barrel Type Long
Finish Type Tin-Plated
Material COPPER

Plated Y

Plating Type Tin Plated

Sub Brand REDUCER SPLICES

Temperature Rating 194
Type Y-R

UPC 781810081938 UPC 12 Digit 7818100819388

Dimensions

Dimension - B Length inch 2.00 in Dimension - L Length Overall 51 mm

mm

Dimension - Length Overall 2.00 in

inch

Dimension - Outside Diameter 0.687 in

inch

Electrical Ratings

Voltage - Maximum 35000

Conductor Related

Conductor - Copper Str Run 350 kcmil Conductor - Copper Str Run 350 kcmil Range Conductor - Copper Str Size 250 kcmil Range Conductor - Copper Str Tap 250 KCMIL 250 kcmil Conductor - Copper Str Tap Range COPPER Conductor - Material CODE Conductor Type Wire Size 250 kcmil

Certifications And Compliance

Certification - CSA Approved No
Certification - ETL No
Certification - UL Recognized No
Certification - cULus No
Standards - RoHS Compliance CM
Status
UL Listed No

Logistics

Carton Quantity 100
Minimum Pack Quantity 1
Pallet Quantity 46400

Product Assets

Catalogs - Full Line BURNDY Catalog Catalogs - Section C - Compression Connections Customer Notices - Prop 65 Notice Sales Drawings - SD..016040-01

