

Compression Splice Reducer

By Burndy Catalog # Y3426R

500 kcmil CU Long Barrel Size Reduced Down To 2/0 AWG Wire Size, Internal Chamfer, Tin Plated, Up to 35kV, BROWN Color Code, 20 or 299 Die Index.



Application

Wire Reducing Splice Adapter Insert

General

Catalog Number Y3426R Color Code Brown

LONG BARREL Connector Type

Die Index 20 Feature - Barrel Type Long Tin-Plated Finish Type COPPER Material

Plated

Plating Type Tin Plated 194

Temperature Rating

781810001059 UPC 12 Digit 7818100010599

Dimensions

Dimension - B Length inch 2.50 in Dimension - L Length Overall 64 mm

mm

Dimension - Length Overall 2.50 in

inch

Dimension - Outside Diameter 0.821 in

Electrical Ratings

Voltage - Maximum 35000

Conductor Related

Conductor - Copper Str Run 500 kcmil Conductor - Copper Str Run 500 kcmil Range Conductor - Copper Str Size 2/0 AWG Range Conductor - Copper Str Tap 2/0 AWG 2/0 AWG Conductor - Copper Str Tap Range COPPER Conductor - Material Conductor Type CODE Wire Size #2/0 AWG

Certifications And Compliance

Certification - CSA Approved Certification - ETL Certification - UL Recognized No Certification - cULus Standards - RoHS Compliance CM Status **UL** Listed

Logistics

Carton Quantity 50 Pallet Quantity 5800

Product Assets

Catalogs - Full Line BURNDY Catalog Catalogs - Section C - Compression Connections Customer Notices - Prop 65 Notice Sales Drawings - SD..016040-01

No

