

Type II Helmets

Type II helmets help provide impact and penetration protection to the top and sides of the head.



Vanguard™ Protective Caps

- Classification:** Type II (CSA and ANSI)
Application: Lateral protection
Shell Material: High-density polyethylene (HDPE)
Available Styles: Slotted Cap w/foam liner
Sizes: Standard (6½ – 8")
Standards: CSA Z94.1-2015 (Type II, Class E); ANSI/ISEA Z89.1-2014 (Type II, Class E)
Certification: Third-party by SEI
Customization: Imprinting and striping available

Vanguard Slotted Caps		
w/Fas-Trac® III Suspension		
WHITE		804940
YELLOW		804939
RED		804944
HI-VIZ ORANGE ¹		804947
BLUE		804946



Please contact MSA Customer Service at 1-800-MSA-2222 for details about Type II Helmets or other head protection or helmet accessory products. You can also visit us on the web at MSAsafety.com.

¹ Super V Cap and Vanguard Cap meet the voluntary standard for hi-visibility as prescribed by ANSI/ISEA Z89.1-2014. Look for the official hi-visibility marking [HV] on the helmet's ANSI label.

Super V® Protective Caps

- Classification:** Type II (CSA); Type I (ANSI)
Application: Lateral Impact (Type II) & Top Impact (Type I and II)
Shell Material: HDPE
Available Styles: Slotted Cap w/foam liner
Sizes: Standard (6½ – 8")
Standards: CSA Z94.1-2015 (Type II, Class E); ANSI/ISEA Z89.1-2014 (Type II, Class E)
Certification: Third-party by SEI
Customization: Imprinting and striping available

Super-V Slotted Caps					
w/ Fas-Trac III Suspension			w/ Fas-Trac III Suspension		
WHITE		C217091	HI-VIZ ORANGE ¹		C217100
YELLOW		C217093	GREEN		C217096
RED		C217095	GOLD		C217098
ORANGE		C217094	BLACK		C217140
BLUE		C217092	SILVER		10025227
NAVY GRAY		C217097			

Fas-Trac III Replacement Suspensions		
	Fas-Trac III for Vanguard	Fas-Trac III for Super-V
	10153386	10126683
Fas-Trac III Sweatband Accessory		
	10153518	<ul style="list-style-type: none"> For use with MSA Fas-Trac® III Suspension Optional, moisture-wicking and washable Can be attached/replaced while suspension is assembled in helmet Sold ONLY in packages of 10

⚠ WARNING

Use only the indicated MSA suspension in your MSA helmet. Do not mix suspension sizes and helmet sizes (i.e., putting a standard sized suspension in a large helmet or any other mismatched combination). Do not use competitor suspensions in MSA helmets. Inspect your suspension frequently. Suspensions should be replaced every 12 months, regardless of inspection results. Replace immediately (along with the helmet), if an impact has occurred. Failure to follow these instructions will reduce the energy absorbing ability of the protective helmet to receive impact, and could result in serious injury or death.

Note: This Bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.

ID 0611-02-MC / February 2017

© MSA 2017 Printed in U.S.A.



MSA – The Safety Company
 1000 Cranberry Woods Drive
 Cranberry Township, PA 16066 USA
 Phone 724-776-8600
www.MSAsafety.com

U.S. Customer Service Center
 Phone 1-800-MSA-2222
 Fax 1-800-967-0398

MSA Canada
 Phone 1-800-672-2222
 Fax 1-800-967-0398

MSA Mexico
 Phone 01 800 672 7222

MSAsafety.com