

DEWALT®

ENGINEERED BY **Powers™**

REMOVABLE AND
REUSABLE FLAT HEAD BOLT
WITH HEX INSERT
FOR FLUSH MOUNT
APPLICATIONS

GRADE 5
CARBON STEEL BOLT

FLEXIBLE COMPRESSION
RING CLAMPS FIXTURE
TO BASE MATERIAL

CARBON STEEL
EXPANSION WEDGE
AND CONE

REMOVABLE AND REUSABLE
LOW PROFILE HEX HEAD BOLT

304 STAINLESS STEEL
SLEEVE AND BOLT

TRIPLE-TINED
EXPANSION SLEEVE PROVIDES
PRIMARY EXPANSION

THREADED BOLT ADVANCES INTO
EXPANDER CONE, FORCING SECTIONS
OUTWARD FOR SECONDARY EXPANSION

TYPICAL APPLICATIONS

- › Column base plates and mechanical equipment
- › Dock bumpers and support ledges
- › Racking and railing attachments

APPROVALS



Full UL listings:
www.DEWALT.com

**ASTM
E488**

Tested In
Accordance
With ASTM
E488

BASE MATERIALS



Normal
Weight
Concrete



Lightweight
Concrete



Grouted
Masonry



Hollow
Masonry



Brick



Stone

HEAVY DUTY SLEEVE ANCHOR

Power-Bolt®

POWER-BOLT® CARBON STEEL FLAT HEAD

CAT #	ANCHOR SIZE	DRILL DIA	MIN EMBED	CTN	MSTR
06981	3/8" x 3-3/4"	3/8"	2"	50	300
06982	3/8" x 5	3/8"	2"	50	300
06983	3/8" x 6"	3/8"	2"	50	300
06984	1/2" x 5"	2-1/2"	2-1/2"	25	150
06987	5/8" x 5-1/2"	5/8"	2-3/4"	15	90

The published length is the overall length of the anchor.

The flat head Power-Bolt anchor has a hex key insert formed in the head of the bolt. Each box contains an Allen wrench which matches the insert size.

POWER-BOLT® 304 STAINLESS STEEL HEX HEAD

CAT #	ANCHOR SIZE	DRILL DIA	MIN EMBED	CTN	MSTR
05902	1/4" - 1-3/4"	1/4"	1-1/4"	100	600
05906	1/4" x 3"	1/4"	1-1/4"	100	600
05910	3/8" x 2-1/4"	3/8"	2"	50	300
05914	3/8" x 3-1/2"	3/8"	2"	50	300
05916	3/8" x 4"	3/8"	2"	50	300
05930	1/2" x 4"	3/8"	2"	50	200
05934	1/2" x 2-3/4"	1/2"	2-1/2"	25	150

The published length is measured from below the washer to the end of the anchor.

RELATED PRODUCTS**DCH293R2DH**

20V MAX* XR® SDS PLUS
ROTARY HAMMER W/DUST
COLLECTION

**DCH273P2DHO**

20V MAX* XR® SDS PLUS ROTARY
HAMMER W/ON-BOARD DUST
EXTRACTOR

**DWH050K**

LARGE HAMMER DUST
EXTRACTION - HOLE CLEANING

**HOLLOW DRILL BIT**

SDS-PLUS AND
SDS-MAX CARBIDE

For 20V MAX Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

1-800-4-DEWALT**www.DEWALT.com**

Copyright ©2019 DEWALT. The following are trademarks for one or more DEWALT power tools, accessories, anchors and concrete adhesives: The yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool.

ICDWBLTSS