


The Timken Company

4500 Mt Pleasant St. NW


N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Timken Part Number 47688 - 47620, Tapered Roller Bearings - TS (Tapered Single) Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.



[Specifications](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

Specifications

Series	47600
Cone Part Number	47688
Cup Part Number	47620
Design Units	Imperial
Bearing Weight	1.700 Kg 3.70 lb
Cage Type	Stamped Steel

Dimensions

d - Bore	83.345 mm 3.2813 in
-----------------	------------------------

D - Cup Outer Diameter	133.350 mm 5.2500 in
B - Cone Width	33.338 mm 1.3125 in
C - Cup Width	26.195 mm 1.0313 in
T - Bearing Width	33.338 mm 1.3125 in

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius¹	3.560 mm 0.14 in
r - Cup Backface "To Clear" Radius²	3.30 mm 0.130 in
da - Cone Frontface Backing Diameter	90.93 mm 4.40 in
db - Cone Backface Backing Diameter	97.03 mm 3.82 in
Da - Cup Frontface Backing Diameter	129.00 mm 5.08 in
Db - Cup Backface Backing Diameter	119.13 mm 4.69 in
Ab - Cage-Cone Frontface Clearance	3 mm 0.12 in
Aa - Cage-Cone Backface Clearance	2 mm 0.08 in
a - Effective Center Location³	-4.30 mm -0.17 in

Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)⁴	55500 N 12500 lbf
---	----------------------

C1 - Dynamic Radial Rating (1 million revolutions)⁵	214000 N 48100 lbf
---	-----------------------

C0 - Static Radial Rating	262000 N 58900 lbf
----------------------------------	-----------------------

C_{a90} - Dynamic Thrust Rating (90 million revolutions)⁶	38400 N 8640 lbf
---	---------------------

Factors

K - Factor⁷	1.44
-------------------------------	------

e - ISO Factor⁸	0.40
-----------------------------------	------

Y - ISO Factor⁹	1.48
-----------------------------------	------

G1 - Heat Generation Factor (Roller-Raceway)	119
---	-----

G2 - Heat Generation Factor (Rib-Roller End)	29.2
---	------

Cg - Geometry Factor	0.127
-----------------------------	-------

¹ These maximum fillet radii will be cleared by the bearing corners.

² These maximum fillet radii will be cleared by the bearing corners.

³ Negative value indicates effective center inside cone backface.

⁴ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.


⁵ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

⁶ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

⁷ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁸ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁹ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.



IMPERIAL UNITS

ISO Factor - e 0.4
ISO Factor - Y 1.48
Bearing Weight 3.7 lbf
Number of Rollers Per Row 23
Effective Center Location -0.17 inch

TIMKEN®

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

47688 - 47620
TS BEARING ASSEMBLY

K Factor 1.44
Dynamic Radial Rating - C90 55500 lbf
Dynamic Thrust Rating - Ca90 38400 lbf
Static Radial Rating - C0 262000 lbf
Dynamic Radial Rating - C1 214000 lbf

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY