



**The Timken Company**

4500 Mt Pleasant St. NW

N. Canton, OH 44720

**Phone:** (234) 262-3000

**E-Mail:** [CustomerCAD@timken.com](mailto:CustomerCAD@timken.com) • **Web site:** [www.timken.com](http://www.timken.com)

## Part Number 6204-2RS-NR-C3, Deep Groove Ball Bearings (6000, 6200, 6300, 6400)

Timken's deep groove ball bearings deliver reliable performance in a wide range of applications and conditions. With super-finished raceways and controlled geometries, our premium design helps ensure consistent quality.



[Specifications](#) | [Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

### Specifications

Clearance	C3
Bore Size d	20 mm
Features	Contact Seals With Snap Ring
Bearing Type	Standard DGBB
Weight	0.100 Kg

### Dimensions

Outside Diameter D	47.000 mm
Outside Ring Width B	14.000 mm


Radius Rs min	1.000 mm
Snap Ring Diameter D2 max	52.700 mm
Snap Ring Width f max	1.120 mm

### Basic Load Ratings

Cr - Dynamic Load Rating	12.8 kN
C0r - Static Load Rating	6.6 kN

### Factors

Grease Reference Speed	15000 rpm
Oil Reference Speed	22000 rpm



## METRIC UNITS

Weight	0.1 kg	<b>TIMKEN®</b>
		<b>THE TIMKEN COMPANY</b> NORTH CANTON, OHIO USA

<b>6204-2RS-NR-C3</b> Deep Groove Ball Bearings (6000, 6200, 6300, 6400)		
Dynamic Load Rating	12800	N
Static Load Rating	6600	N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY