



U.S. Tsubaki Power Transmission, LLC

301 E. Marquardt Dr.

Wheeling, IL 60090

Phone: 847.459.9500 or 800.323.7790

Fax: 847.459.9515

Email: sales@ustsubaki.com


Website: www.ustsubaki.com

[All Categories](#) > [Sprockets](#) > [Roller Chain Sprockets](#) > [ANSI Single Pitch Sprockets](#) > [No. 160 - 2" Pitch Sprockets](#) > [No. 160 - 2" Pitch - Plain Bore Sprockets](#) > [Item # 160B20](#)

ITEM # 160B20, NO. 160 - 2" PITCH - PLAIN BORE SPROCKETS

No. 160, B Style, 1.500" plain bore

All dimensions are nominal values and for reference only



[Specifications](#) | [Chain Technical Data](#) | [Sprocket Diameters](#)

Specifications

Stock Bore Diameter	1.500 in
Hub Diameter¹	7.000 in
LTB	2.750 in
Style	B

No. Teeth	20
Max. Bore²	5.250 in
Weight	56.000 lb
Tooth Nominal Width	1.156 in
Hardened Teeth	Yes

Chain Technical Data

Pitch	2.000 in
Chain Size	160

Sprocket Diameters

Outside Diameter	13.830 in
Pitch Diameter	12.784 in
Caliper Diameter	11.659 in

¹ Hub diameter may vary to suit bore sizes

² Dimensions shown allow for standard keyway with set screw at 90°