



U.S. Tsubaki Power Transmission, LLC

301 E. Marquardt Dr.

Wheeling, IL 60090

Phone: 847.459.9500 or 800.323.7790

Fax: 847.459.9515

Email: sales@ustsubaki.com


Website: www.ustsubaki.com

[All Categories](#) > [Sprockets](#) > [Roller Chain Sprockets](#) > [ANSI Single Pitch Sprockets](#) > [No. 50 - 5/8" Pitch Sprockets](#) > [No. 50 - 5/8" Pitch - Plain Bore Sprockets](#) > [Item # 50B45](#)

ITEM # 50B45, NO. 50 - 5/8" PITCH - PLAIN BORE SPROCKETS

No. 50, B Style, .750" plain bore

All dimensions are nominal values and for reference only



[Specifications](#) | [Chain Technical Data](#)

Specifications

Stock Bore Diameter	0.750 in
Hub Diameter	3.750 in
LTB	1.250 in

Style	B
No. Teeth	45
Outside Diameter	9.310 in
Pitch Diameter	9.159 in
Caliper Diameter	8.759 in
Max. Bore¹	2.500 in
Weight	5.920 lb
Tooth Nominal Width	0.343 in
Hardened Teeth	Yes

Chain Technical Data

Pitch	0.625 in
Chain Size	50

¹ Dimensions shown allow for standard keyway with set screw at 90°