

# SAFETY DATA SHEET

## BOLT-OUT (Aerosol)

### Section 1. Identification

**GHS product identifier** : BOLT-OUT  
**Product code** : 53-D 892 (400 ml)  
**SDS no.** : L-08E  
**Product type** : Aerosol.

#### Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** : Penetrating lubricant.

**Manufacturer** : Walter Surface Technologies Inc.  
5977 Trans Canada Highway  
Pointe-Claire, QC H9R 1C1  
Canada  
info@walter.com  
www.walter.com  
General Information: 1-888-592-5837

**Emergency telephone number (with hours of operation)** : INFOTRAC® 1-800-535-5053. International call collect: 1-352-323-3500  
24 hours/day, 7 days/week.

### Section 2. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Classification of the substance or mixture** : FLAMMABLE AEROSOLS - Category 1  
GASES UNDER PRESSURE - Compressed gas  
SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A  
ASPIRATION HAZARD - Category 1

#### GHS label elements

**Hazard pictograms** :



**Signal word** : Danger

**Hazard statements** : H222 - Extremely flammable aerosol.  
H280 - Contains gas under pressure; may explode if heated.  
H319 - Causes serious eye irritation.  
H315 - Causes skin irritation.  
H304 - May be fatal if swallowed and enters airways.

#### Precautionary statements

## Section 2. Hazards identification

- Prevention** : P280 - Wear protective gloves. Wear eye or face protection.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P264 - Wash hands thoroughly after handling.  
P251 - Pressurized container: Do not pierce or burn, even after use.
- Response** : P301 + P310 + P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting.  
P302 + P352 + P362+P364 - IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.  
P332 + P313 - If skin irritation occurs: Get medical attention.  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 - If eye irritation persists: Get medical attention.
- Storage** : P405 - Store locked up.  
P410 - Protect from sunlight.  
P412 - Do not expose to temperatures exceeding 50°C/122°F.  
P403 - Store in a well-ventilated place.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Hazards not otherwise classified** : None known.

## Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture  
**Product code** : 53-D 892 (400 ml)

Ingredient name	%	CAS number
Kerosine (Petroleum)	80 - 100	8008-20-6

United States: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

Canada: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with the amended HPR as of April 2018.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately.
- Skin contact** : Flush contaminated skin with plenty of water. Get medical attention if symptoms occur.

## Section 4. First aid measures

- Ingestion** : Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation.
- Ingestion** : May be fatal if swallowed and enters airways.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : Adverse symptoms may include the following:  
nausea or vomiting

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : In case of fire, use foam, dry chemical or carbon dioxide.
- Unsuitable extinguishing media** : Do not use water jet.

- Specific hazards arising from the chemical** : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

## Section 5. Fire-fighting measures

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

- Spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking

## Section 7. Handling and storage

- tools. Empty containers retain product residue and can be hazardous.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

#### United States

##### Occupational exposure limits

Ingredient name	Exposure limits
Kerosine (Petroleum)	<b>NIOSH REL (United States, 10/2016).</b> TWA: 100 mg/m <sup>3</sup> 10 hours. <b>ACGIH TLV (United States, 3/2017). Absorbed through skin.</b> TWA: 200 mg/m <sup>3</sup> , (as total hydrocarbon vapor) 8 hours.

#### Canada

##### Occupational exposure limits

Ingredient name	Exposure limits
Kerosine (Petroleum)	<b>CA British Columbia Provincial (Canada, 6/2017). Absorbed through skin.</b> TWA: 200 mg/m <sup>3</sup> , (as total hydrocarbon vapour) 8 hours. <b>CA Ontario Provincial (Canada, 1/2018). Absorbed through skin.</b> TWA: 200 mg/m <sup>3</sup> 8 hours. <b>CA Alberta Provincial (Canada, 4/2009). Absorbed through skin.</b> 8 hrs OEL: 200 mg/m <sup>3</sup> , (as total hydrocarbon vapour) 8 hours. <b>CA Saskatchewan Provincial (Canada, 7/2013). Absorbed through skin.</b> STEL: 250 mg/m <sup>3</sup> , (measured as total hydrocarbon vapor) 15 minutes. TWA: 200 mg/m <sup>3</sup> , (measured as total hydrocarbon vapor) 8 hours.

- Appropriate engineering controls** : No personal respiratory protective equipment normally required. Avoid breathing dust/fume/gas/mist/vapors/spray. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

### Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

## Section 8. Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.  
Recommended: Nitrile gloves. (Permeation time > 8 hours)
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a NIOSH/MSHA approved respirator if there is a risk of exposure at levels exceeding the exposure limits. Advice should be sought from respiratory protection specialists.

## Section 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid. [Aerosol.]
- Color** : Dark gray.
- Odor** : Characteristic.
- Odor threshold** : Not available.
- pH** : Not applicable.
- Melting point** : Not available.
- Boiling point** : Not applicable.
- Flash point** : Closed cup: -60°C (-76°F)
- Evaporation rate** : Not applicable.
- Flammability (solid, gas)** : Extremely flammable aerosol.
- Lower and upper explosive (flammable) limits** : Lower: 1.4%  
Upper: 32%
- Vapor pressure** : 400 kPa (3000.2 mm Hg) [room temperature]
- Vapor density** : Not available.
- Relative density** : 0.791 g/ml @ 20°C (68°F)
- Solubility** : Insoluble in the following materials: cold water and hot water.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : 510°C (950°F)
- Decomposition temperature** : Not available.
- Viscosity** : Not available.
- Flow time (ISO 2431)** : Not available.
- VOC content** : 98.5 % (w/w)
- Aerosol product**
- Type of aerosol** : Spray

## Section 9. Physical and chemical properties

**Heat of combustion** : 42.52 kJ/g

## Section 10. Stability and reactivity

**Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

**Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : Avoid all possible sources of ignition (spark or flame).

**Incompatible materials** : Reactive or incompatible with the following materials: oxidizing materials and acids.

**Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Kerosine (Petroleum)	LD50 Oral	Rat	15 g/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Kerosine (Petroleum)	Skin - Moderate irritant	Rabbit	-	0.5 ml	-
	Skin - Moderate irritant	Rabbit	-	24 hours 100%	-
	Skin - Severe irritant	Rabbit	-	500 mg	-

#### Sensitization

There is no data available.

#### Mutagenicity

There is no data available.

#### Carcinogenicity

##### Classification

Product/ingredient name	OSHA	IARC	NTP
Kerosine (Petroleum)	-	3	-

#### Reproductive toxicity

There is no data available.

#### Teratogenicity

There is no data available.

#### Specific target organ toxicity (single exposure)

There is no data available.

#### Specific target organ toxicity (repeated exposure)

There is no data available.

#### Aspiration hazard

## Section 11. Toxicological information

Name	Result
Kerosine (Petroleum)	ASPIRATION HAZARD - Category 1

**Information on the likely routes of exposure** : Dermal contact. Eye contact. Inhalation. Ingestion.

**Potential acute health effects**

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation.
- Ingestion** : May be fatal if swallowed and enters airways.

**Symptoms related to the physical, chemical and toxicological characteristics**

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : Adverse symptoms may include the following:  
nausea or vomiting

**Delayed and immediate effects and also chronic effects from short and long term exposure**

**Short term exposure**

- Potential immediate effects** : No known significant effects or critical hazards.
- Potential delayed effects** : No known significant effects or critical hazards.

**Long term exposure**

- Potential immediate effects** : No known significant effects or critical hazards.
- Potential delayed effects** : No known significant effects or critical hazards.

**Potential chronic health effects**

- General** : No known significant effects or critical hazards.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

**Numerical measures of toxicity**

**Acute toxicity estimates**

There is no data available.

## Section 12. Ecological information

### Toxicity

There is no data available.

### Persistence and degradability

There is no data available.

### Bioaccumulative potential

There is no data available.

### Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
<b>UN number</b>	UN1950	UN1950	UN1950	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable (each not exceeding 1 L capacity)	Aerosols, flammable (each not exceeding 1 L capacity)	Aerosols, flammable (each not exceeding 1 L capacity)	Aerosols, flammable (each not exceeding 1 L capacity)
<b>Transport hazard class(es)</b>	2.1 	2.1 	2.1 	2.1 
<b>Packing group</b>	-	-	-	-
<b>Environmental hazards</b>	No.	No.	No.	No.

**AERG** : 126

### Additional information

## Section 14. Transport information

**TDG Classification** : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2).

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. Protect from freezing. Freezing will damage product and render it unusable.

## Section 15. Regulatory information

**U.S. Federal regulations** : **TSCA 8(a) PAIR:** Benzaldehyde  
**United States inventory (TSCA 8b):** All components are listed or exempted.  
**Clean Air Act (CAA) 112 regulated flammable substances:** Propane

**Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Not listed

**Clean Air Act Section 602 Class I Substances** : Not listed

**Clean Air Act Section 602 Class II Substances** : Not listed

**DEA List I Chemicals (Precursor Chemicals)** : Not listed

**DEA List II Chemicals (Essential Chemicals)** : Not listed

**SARA 302/304**

**Composition/information on ingredients**

No products were found.

**SARA 304 RQ** : Not applicable.

**SARA 311/312**

**Classification** : FLAMMABLE AEROSOLS - Category 1  
 GASES UNDER PRESSURE - Compressed gas  
 SKIN CORROSION/IRRITATION - Category 2  
 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A  
 ASPIRATION HAZARD - Category 1

**Composition/information on ingredients**

Name	Classification
Kerosine (Petroleum)	FLAMMABLE LIQUIDS - Category 3 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A ASPIRATION HAZARD - Category 1

**SARA 313**

There is no data available.

**State regulations**

**Massachusetts** : The following components are listed: Kerosine (Petroleum); Carbon dioxide, gas; Propane

**New York** : None of the components are listed.

## Section 15. Regulatory information

- New Jersey** : The following components are listed: Kerosine (Petroleum); Carbon dioxide, gas; Propane
- Pennsylvania** : The following components are listed: Kerosine (Petroleum); Carbon dioxide, gas; Propane

**California Prop. 65**

No products were found.

**Canada**

**Canadian lists**

- Canadian NPRI** : The following components are listed: Propane
- CEPA Toxic substances** : The following components are listed: Carbon dioxide, gas
- Canada inventory (DSL NDSL)** : All components are listed or exempted.

- Australia** : All components are listed or exempted.
- China** : All components are listed or exempted.
- Europe** : All components are listed or exempted.
- New Zealand** : All components are listed or exempted.
- Philippines** : All components are listed or exempted.
- Republic of Korea** : All components are listed or exempted.
- Taiwan** : All components are listed or exempted.

## Section 16. Other information

**Procedure used to derive the classification**

Classification	Justification
FLAMMABLE AEROSOLS - Category 1	On basis of test data
GASES UNDER PRESSURE - Compressed gas	On basis of test data
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A	Calculation method
ASPIRATION HAZARD - Category 1	Expert judgment

**History**

- Date of issue mm/dd/yyyy** : 09/15/2018
- Date of previous issue** : 11/30/2015
- Version** : 2
- Prepared by** : KMK Regulatory Services Inc.

**Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.