Oil Only Absorbency

BradyID.com/s35

Catalog #

Pads

SXT100

SXT300

SXT200

Rolls SXT30DP

SXT15P



Туре

Heavy Wt. Pad

Medium Wt. Pad

Light Wt. Pad

Heavy Wt. Roll

Heavy Wt. Roll

SXT[®] Oil Only Absorbents

- Ideal absorbent where durability, abrasion resistance and low linting are required
- Floats indefinitely even when saturated with oil
- Durable 3-ply meltblown polypropylene construction with abrasion-resistant top and bottom coverstock layers

Absorbency

Factor (gl/gs)

12

12

12

12

12

· Extra strength allows for wringing and re-use

Features:

Perforated

Yes, 7.5"

Yes, 7.5

Yes, 7.5

- · For Oils, Coolants, Solvents and Oil-based Fluids
- Top & Bottom Coverstock (3-Ply) · High Durability & Low Linting

Absorbency

19.5

17

37

18

31.5

Capacity (gal)

Floats Indefinitely

Yes. 15" and every 15"

Yes, every 18"

· Perforated & Dimpled · Heavy, Medium & Light Weights

Shipping Wt (lbs)

14.5

10

18

26.5

14

Pallet

Qty.

30

30

22

12

24

Quantity

100/case

100/case

200/case

1/case

1/case

• Cost: \$ \$ \$

Absor	Specialty Product: For Marine Use	 ENV[®] Oil Absorbents Highly economical, contractor grade absorbent for oil clean-up on land or water Floats indefinitely even when saturated with oil Efficient single-ply of MAXX[®] Technology – absorption and strength without the extra weight Packaged in a green bag to streamline absorbent identification in your facility 				
5						
D		Features:				
phts		 For Oils, Coolants, Solvents and Oil-based Fluids No Coverstock (1-Ply) Light Durability & High Linting Floats Indefinitely 	 Non-Dimpled for max surface absorbtion area Heavy, Medium & Light Weights Cost: \$ 			

Size

15"x19'

15"x19'

15"x19"


30"x150'

15"x150

- or oil clean-up on land or water
- ption and strength without the
- nt identification in your facility
 - y, Medium & Light Weights
 - \$

Catalog #	Туре	Size	Perforated	Absorbency Factor (gl/gs)	Absorbency Capacity (gal)	Shipping Wt (Ibs)	Pallet Qty.	Quantity
Pads								
ENV50	Medium Wt. Pad	30"x30"	No	20	50	19	14	50/bale*
ENV100	Heavy Wt. Pad	15"×19"	No	20	33	12.5	30	100/bale*
ENV300	Medium Wt. Pad	15"x19"	No	18	23	10	30	100/bale*
ENV200	Light Wt. Pad	15"x19"	No	23	51	16	24	200/bale*
ENV500	Light Wt. Pad	15"x19"	No	23	24.5	8	30	100/bale*
MXO1000	Light Wt. Pad	15"x19"	Yes, 7.5"	23	24	11	30	100/case
Rolls								
ENV150	Medium Wt. Roll	30"x150'	No	15	44	22	18	1/bale*

*ENV Oil Absorbents packaged in a green bag.



Static Resistant Oil Absorbents

- Oil only absorbents specially treated to resist static electricity build up around flammable liquid or delicate electronics
- · Oil only absorbency for petroleum-based oils, solvents and other non-water soluble liquids - making it idea for outdoor use
- Economical single-ply pads & rolls made of oil only meltblown polypropylene
- Meets National Fire Protection Association specifications

Features:

- · For Oils, Coolants, Solvents and Oil-based Fluids
- No Coverstock (1-Ply)
- Light Durability & High Linting
- · Non-Dimpled for max surface absorbtion area
- · Heavy Weights • Cost: \$ \$ \$

Catalog #	Туре	Size	Perforated	Absorbency Factor (gl/gs)	Absorbency Capacity (gal)	Shipping Wt (lbs)	Pallet Qty.	Quantity
Pads								
SR3625	Heavy Wt. Pad	30"x30"	No	13	16	9	14	25/bale
SR100	Heavy Wt. Pad	15" x19"	No	13	26	14.5	30	100/bale
Rolls								
SR3600	Heavy Wt. Roll	30"x150'	No	15	44	22	18	1/bale